

County Surveyor's Record, Douglas County, Oregon

1

Dependent Resurvey, Portion of Subdivisional Lines of T. 24 S.,
R. 4 W., Will. Mer.
Executed by Lynn M. Roseberry, Cadastral Surveyor

CHAINS

Under Special Instructions dated June 21, 1957.

(Restoring the 1855 survey by Gordon and Gardner, and the 1896-97
survey by Oscar Thiel.)

The cor. of secs. 11, 12, 13, and 14, is perpetuated by a cedar stake, 3 ft. long, 2 ins. square, firmly set 12 ins. in the ground, from which the remaining original bearing trees:

A cedar, 32 ins. diam., bears S. 68° E., 60 lks. dist., with scribe marks R4W visible on partly opened blaze. (Record calls for a redwood.)

A cedar, 20 ins. diam., bears S. 11° W., 22½ lks. dist., with a healed blaze. (Record, a redwood, bears S. 10° W., 21 lks. dist.)

A turned out fir snag, 30 ins. diam., bears N. 49° W., 38 lks. dist., with scribe marks S R4W visible on partly opened blaze.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap marked

T24S R4W
S 11 | S 12
S 14 | S 13
1957

from which

A fir, 17 ins. diam., bears N. 18° E., 29 lks. dist., marked T24S R4W S12 BT.

A fir, 27 ins. diam., bears N. 7° W., 104 lks. dist., marked T24S R4W S11 BT.

Reset the cedar stake alongside the iron post.

N. 0° 06' E., bet. secs. 11 and 12, marking and blazing the true line.

Descend 81 ft. along W. slope, through timber and undergrowth.

4.86 Wet ravine, drains NW.; ascend 1 ft. along W. slope.

13.10 Ravine, drains S. 70° W.; ascend 90 ft. along broken W. slope.

22.39 Top of ascent, slopes W.; descend 170 ft. along W. slope changing to NW. slope.

25.90 Edge of timber, bears NE. and SW.; enter logged area.

30.86 Wet ravine, drains NW.; descend 56 ft. along W. slope.

36.89 Spring, drains NW.; desc. 27 ft. along W. slope.

43.16 Mill Creek, 8 lks. wide, course S. 30° W.; ascend 24 ft. over SE. slope, of creek bottom.

45.29 Branch, 4 lks. wide, course SE.; ascend 61 ft. over SE. slope, through timber and undergrowth.

47.62 Abandoned logging road, 20 lks. wide, bears N. 30° E. and S. 30° W.

50.31 The ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap marked