

Dependent Resurvey, Portion of Subdivisional Lines, T. 24 S.,
R. 4 W.

CHAINS

T24S R4W

$\frac{1}{2}$
 S 11 | S 12
 1957

from which

A fir, 7 ins. diam., bears S. 31° E., $53\frac{1}{2}$ lks. dist.,
marked $\frac{1}{4}$ S12 BT.

A hemlock, 8 ins. diam., bears N. $49\frac{1}{2}$ W., 17 lks. dist.,
marked $\frac{1}{4}$ S11 BT.

Ascend 67 ft. over SE. slope.

- 55.96 Same road, bears N. and S. 10° E.
- 56.72 Same road, bears N. 20° E. and S.
- 59.35 Spring branch, 2 lks. wide, course SW.; ascend 23 ft. over S. slope.
- 63.64 Branch, 4 lks. wide, course S. 10° W.; from N. 10° W.; ascend 58 ft.
over gradual S. slope.
- 69.97 Foot of steep ascent, bears NW. and E.; ascend 229 ft. over S. slope.
- 76.67 Spur, slopes SW.; descend 70 ft. along rocky W. slope.
- 83.07 Branch, 4 lks. wide, course S. 20° W.; ascend 133 ft. over SE. slope.
- 94.27 Spring branch, 2 lks. wide, course SE.; ascend 119 ft. over S. slope.
- 100.75 The cor. of secs. 1, 2, 11, and 12, perpetuated by a cedar stake,
18 ins. long, $1\frac{1}{2}$ ins. square, firmly set 6 ins. in the ground,
from which the original bearing trees:
- A fir, 18 ins. diam., bears N. $23\frac{1}{2}$ E., 11 ins. dist., with
scribe marks 24S 4 1 BT visible on partly opened blaze. (Rec-
ord bearing, N. $32\frac{1}{2}$ E.)
- A fir, 36 ins. diam., bears S. 66° E., 18 lks. dist., with a
healed blaze. (record bearing S. $68\frac{1}{2}$ E.)
- A fir, 32 ins. diam., bears S. 47° W., 29 lks. dist., with scribe
marks 11 visible on partly opened blaze. (Record bearing,
S. 44° W.)
- A fir, 30 ins. diam., bears N. 12° W., 93 lks. dist., with a
healed blaze.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground,
with brass cap marked

T24S R4W
 S 2 | S 1
 S 11 | S 12
 1957

Reset the cedar stake alongside the iron post.

Land, mountainous. Soil, rocky loam and clay. Timber, fir, cedar,
hemlock, madrona; with maple, yew and alder in the creek bottom.
Undergrowth, vine maple, reproduction, hazel, arrowwood and ferns.