

County Surveyor's Record, Douglas County, Oregon

3

Dependent Resurvey, Portion of Subdivisional Lines, T. 24 S.,
R. 4 W.

CHAINS	
	From the closing cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	N. 61° 57' W., bet. secs. 1 and 12.
	Ascend 102 ft. along NE. slope, between logged area and old growth timber.
8.63	Spur, slopes S.; descend 185 ft. along SW. slope.
22.36	Wet ravine, drains W.; ascend 3 ft. along broken SW. slope.
25.09	Ridge, bears E. and W. curving to SW.; descend 116 ft. over NW. slope.
31.44	Wet ravine, drains W.; descend 34 ft. along SW. slope.
32.92	Branch, 4 ins. wide, course S. 50° W.; ascend 31 ft. along S. slope.
36.09	Top of large rock and edge of timber, bears S. 60° E. and W.; ascend 262 ft. over steep S. slope.
46.43	The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented by a fir, 27 ins. diam., marked with a healed blaze on the N. side, from which the original bearing trees: A fir, 16 ins. diam., bears N. 25° E., 36 lks. dist., marked $\frac{1}{4}$ S BT on opened blaze. (Record bearing, N. 51° E.) A cedar, 6 ins. diam., bears S. 42° W., 24 lks. dist., marked $\frac{1}{4}$ S on partly rotted blaze. (Record bearing, S. 45° W.) And a new bearing tree, A fir, 19 ins. diam., bears S. 9 $\frac{1}{2}$ ° W., 30 lks. dist., marked $\frac{1}{4}$ S12 BT.
	N. 89° 02' W., beginning new measurement.
	Ascend 136 ft. over SE. slope.
6.39	Spur ridge, bears N. 50° E. and S. 50° W.; descend 384 ft. over NW. slope.
17.42	Edge of timber, bears N. 10° E. and W.; descend 329 ft. over W. slope.
31.45	Branch, 2 lks. wide, course SW.; ascend 9 ft. along S. slope.
39.38	The cor. of secs. 1, 2, 11, 12. Land, mountainous. Soil, rocky clay and loam. Timber, red and incense cedar, hemlock, maple, chinquapin and alder. Undergrowth, vine maple, arrowwood, dogwood, salal and ferns.
	N. 0° 19' E., bet. secs. 1 and 2.
	Ascend 525 ft. over S. slope changing to steep SE. slope, through heavy timber and light undergrowth.
17.26	Spur ridge, bears N. 30° E. and S. 30° W.; ascend 70 ft. along W. slope.
25.06	Top of ascent, slopes NW.; descend 193 ft. over steep N. slope.
28.63	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.