

County Surveyor's Record, Douglas County, Oregon

T. 29 S., R. 5 W., Will. Mer., Ore.
 Dependent Resurvey of Portion of East Boundary, T. 29 S., R. 5 W.
 Executed by Irving Zirpel, Jr., Cadastral Surveyor
 Under Special Instructions dated June 11, 1957.

CHAINS

(Restoring the 1851 survey of C. E. Freeman and partial retracement by W. F. Briggs in 1899.)

Beginning at the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. determined at the record dist. from three remaining original bearing trees, as follows:

A turned-out, black oak, 11 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 55 lks. dist., with an opened and rotted blaze. (Record bearing N. $55\frac{1}{2}^{\circ}$ E.)

A black oak, 16 ins. diam., bears S. 70° E., 32 lks. dist., with a healed blaze. (Record bearing S. 64° E.)

A madrone crown, bears N. 17° W., 15 lks. dist. (Record bearing N. 30° W.)

At corner point

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S	
R5W	R4W
S 25	S 30
S 36	S 31
1957	

from which new bearing trees:

A fir, 10 ins. diam., bears N. 58° E., 64 lks. dist., marked T29S R4W S30 BT.

A fir, 8 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 46 lks. dist., marked T29S R4W S31 BT.

A fir, 10 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 47 lks. dist., marked T29S R5W S36 BT.

A fir, 12 ins. diam., bears N. $46\frac{1}{4}^{\circ}$ W., 49 lks. dist., marked T29S R5W S25 BT.

From this point a locally established and recorded cor., monumented with an iron post, 1 in. diam., firmly set, 6 ins. above ground, bears N. 60° E., $3\frac{1}{2}$ lks. dist. This cor. was set by J. Markham in 1951.

from which locally established bearing trees:

A black oak, 12 ins. diam., bears N. $87\frac{1}{4}^{\circ}$ E., 41 lks. dist., with BT visible on a partially healed blaze.

A fir, 5 ins. diam., bears S. 24° E., 17 lks. dist., with BT visible on a partially healed blaze.

A fir, 7 ins. diam., bears S. $20\frac{3}{4}^{\circ}$ W., $37\frac{1}{2}$ lks. dist., with BT visible on a partially healed blaze.

A madrone, 22 ins. diam., bears N. 28° W., 22 lks. dist., with partially healed blaze.

N. $1^{\circ} 04'$ E., between secs. 25 and 30, marking and blazing the true line.

Ascend 12 ft. along W. slope through heavy timber and scattering undergrowth.

12.30

Spur ridge, bears N. 5° W. and S. 5° E.; desc. 210 ft. along E. slope.