

Dependent Resurvey of Portion of East Boundary, T. 29 S., R. 5 W.

CHAINS

N. 0° 24' E., between secs. 19 and 24.

Asc. 14 ft. over bottom land of S. Myrtle Creek.

2.07 Board fence and edge of field, bears E. and W.; asc. 190 ft. over SE. slope.

2.33 Barbed-wire fence, bears E. and W.

12.13 Woven-wire and 2 strand barbed-wire fence, bears N. 10° E. and S. 10° W. Leave field.

12.67 Center line of asphaltic S. Myrtle Creek Road, 32 lks. wide, bears N. 20° E. and S. 10° W.

13.32 N. edge of road cut and edge of timber, bears N. 20° E. and S. 10° W.

14.18 Woven-wire fence, bears S. 85° W. and N. 85° E.

14.75 Center line of dirt drive-way, bears N. 5° E. and S. 80° W.

15.13 Woven-wire fence, extends W. and N., continue along W. side of fence.

20.74 Top of ascent, slopes SE.; desc. 39 ft. along E. slope.

24.12 Power line, bears S. 60° E. and N. 60° W.

29.80 Foot of descent slopes E.; asc. 22 ft. along E. slope.

32.08 Top of ascent slopes E.; desc. 14 ft. along E. slope.

38.76 Creek, 1 lk. wide, course SE.; asc. 4 ft. over SW. slope.


38.92 Woven-wire fence, extends W.

30.06 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, perpetuated by a rifle barrel and vise screw, 6 ins. below surface of the ground, This cor. was perpetuated by F. C. Frear, D.S.C. in 1918 from the original BTs., the only remaining one as follows:

A white oak, 30 ins. diam., bears S. 75° W., 180 lks. dist., with a healed blaze that has been partially opened, no scribe marks visible.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked



from which

A fir, 26 ins. diam., bears N. 48° E., 355 lks. dist., marked $\frac{1}{4}$ S19 BT.

An incense cedar, 25 ins. diam., bears S. 73° W., 159 lks. dist., marked $\frac{1}{4}$ S24 BT.

Deposit old corner material alongside iron post.

N. 0° 39' E., beginning new measurement.

Asc. 464 ft. over SW. slope.