


Dependent Resurvey of Portion of East Boundary, T. 29 S., R. 5 W.

CHAINS	
26.52	Woven-wire fence, with steel posts, bears N. 80° E. and S. 80° W.
27.00	N. Myrtle Creek Road, asphaltic, 32 lks. wide, bears N. 80° E. and S. 80° W.
27.47	Woven-wire fence with steel post, bears N. 80° E. and S. 80° W.
40.33	The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, perpetuated at record dist. from 2 original bearing trees by an iron post, 1 in. diam., 18 ins. above ground, firmly set, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked

County Surveyor



from which original BTs.

A black oak, 40 ins. diam., bears S. 47° E., 40 lks. dist., with scribe marks $\frac{1}{4}$ visible on opened blaze. (Record bearing S. 50° E.)


A white oak, 26 ins. diam., bears N. 24 $\frac{1}{2}$ ° W., 38 lks. dist., with an opened and rotten blaze, no scribe marks visible; remarked $\frac{1}{4}$ S13 CS BT. by county surveyor. (Record bearing N. 78° W.)

Newly established BT. by county surveyor

A white oak, 22 ins. diam., bears S. 82 $\frac{1}{4}$ ° E., 56 lks. dist., marked $\frac{1}{4}$ S18 CS BT. on a double blaze.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked



Deposit county surveyor cor. alongside iron post.

Land, bottom land of N. Myrtle Creek. Soil, granular clay and loam on bottom land. Timber, fir, oak, madrone, maple, cedar and pine; undergrowth, poison-oak and small reproduction.

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.
(Restoring the 1855 survey by Nathaniel Ford.)

Point for the cor. of secs. 35 and 36, only, on S. bdy. of Tp., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked