

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS

T29S R5W  
 S 35 | S36  
 T30S R5W  
 S 2  
 1957

from which

A fir, 15 ins. diam., bears N. 46° E., 75 lks. dist.,  
 marked T29S R5W S36 BT.

A fir, 13 ins. diam., bears N. 87½° W., 42 lks. dist.,  
 marked T29S R5W S35 BT.

From this point the corner of Tps. 29 and 30 S., Rs. 4 and 5 W.,  
 bears N. 89° 33' E., 83.09 chs. dist., perpetuated with an iron  
 post, 1 in. diam., 10 ins. above ground, firmly set, from which  
 the original bearing trees as follows:

An incense cedar, 15 ins. diam., bears N. 60° E., 3 lks. dist.,  
 with W S31 visible on partially opened blaze. (Record bearing  
 N. 75° E.)

An incense cedar, 32 ins. diam., bears S. 65½° E., 67 lks.  
 dist., with a healed blaze. (Record bearing S. 65° E.)

An incense cedar, 25 ins. diam., bears S. 76¾° W., 35 lks. dist.,  
 with a healed blaze. (Record bearing S. 79° W.)

An incense cedar, 23 ins. diam., bears N. 16¼° W., 20 lks. dist.,  
 with a healed blaze. (Record.)

A locally established BT., a fir, 45 ins. diam., bears S. 78° E.,  
 19 lks. dist., bark scribed T30S R4W S6 BT.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground,  
 with brass cap marked

T29S  
 R5W | R4W  
 S 36 | S 31  
 S 1 | S 6  
 T30S  
 1957

From this same point the cor. of secs. 34 and 35, only, on S. bdy.  
 of Tp., bears S. 89° 33' W., 78.50 chs. dist., determined at  
 record bearing and distance from the only remaining bearing tree,  
 as follows:

A madrone, 23 ins. diam., bears N. 45° E., 170 lks. dist.,  
 with rotted center, no scribe marks visible.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground,  
 to bed rock, with brass cap marked

T29S R5W  
 S 34 | S35  
 T30S R5W  
 S 3  
 1957

from which