

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS

A fir, 12 ins. diam., bears N. 22° E., 22 lks. dist., marked T29S R5W S35 BT.

A fir, 13 ins. diam., bears N. 74½° W., 35½ lks. dist., marked T29S R5W S34 BT.

From this point a locally established and recorded cor. bears N. 45° E., 22 lks. dist., monumented with an iron post, 1 in. diam., 12 ins. above ground,

from which

A locally established BT., a turned-out fir, 12 ins. diam., bears N. 80° E., 39 lks. dist., with illegible scribe marks visible on a partially healed blaze.

A locally established BT., a madrone, 11 ins. diam., bears N. 9½° W., 38 lks. dist., bark scribed S34 T29S R5W BT.

N. 4° 25' E., between secs. 35 and 36, marking and blazing the true line.

Descend 34 ft. over NW. slope through second growth timber and scattering undergrowth.

- 1.84 Ravine, course S. 70° W., asc. 205 ft. over SW. slope.
- 9.34 Spur, slopes SW.; asc. 6 ft. along W. slope.
- 12.83 Ridge, bears N. 30° W. and S. 30° E.; desc. 74 ft. over general N. slope.
- 16.65 Spur, slopes NW.; desc. 155 ft. over N. slope.
- 17.04 Line tree, a fir, 43 ins. diam., marked with 3 hacks on N. and S. faces.
- 19.13 Enter logged area, edge bears E. and W.
- 21.51 Small ravine, course N. 40° W.; desc. 117 ft. over NW. slope.
- 25.78 Abandoned tractor road, bears NE. and SW., also ravine, course NE., asc. 53 ft. over SE. slope.
- 33.13 Top of ascent slopes E.; desc. 31 ft. over NE. slope.
- 35.70 Ravine, course S. 70° E.; asc. 41 ft. over SE. slope.
- 36.52 Spur, slopes E.; desc. 17 ft. over NE. slope.
- 39.855 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S R5W

S 35 | S 36

1957

from which

A fir, 14 ins. diam., bears N. 54½° E., 341 lks. dist., marked ¼ S 36 BT.

A fir, 12 ins. diam., bears S. 50½° W., 110 lks. dist., marked ¼ S 35 BT.