

County Surveyor's Record, Douglas County, Oregon

9

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS

- Desce, 6 ft. over NE. slope.
- 40.08 Ravine, course S. 80° E.; asc. 94 ft. over SE. slope.
- 44.46 Spur, slopes E.; desc. 387 ft. over N. slope.
- 54.12 Intermittent Creek, 4 lks. wide, course E. and also tractor road, bears N. 70° E. and W.; asc. 260 ft. over SE. slope.
- 65.05 Tractor road, course NE. and SW.
- 65.89 Spur, slopes SE.; desc. 155 ft. over NE. slope.
- 66.29 Tractor road, bears S. 70° E. and W.
- 71.05 Ravine, course E.; asc. 12 ft. over SE. slope.
- 72.54 Spur, slopes E.; desc. 92 ft. over NE. slope.
- 75.86 Ravine, course E.; asc. 32 ft. over SE. slope.
- 77.91 Spur, slopes E.; desc. 32 ft. over N. slope along tractor road which bears N. and S.
- 79.71 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

S
T29~~W~~ R5W
S 26 | S 25
S 36 | S 36.
1957

from which.

A fir, 9 ins. diam., bears N. 72° E., 75½ lks. dist., marked T29S R5W S25 BT.

A fir, 11 ins. diam., bears S. 23° E., 53½ lks. dist., marked T29S R5W S36 BT.

A fir, 9 ins. diam., bears S. 76½° W., 62 lks. dist., marked T29S R5W S35 BT.

A madrone, 8 ins. diam., bears N. 7° W., 74 lks. dist., marked T29S R5W S26 BT.

From this point the cor. of secs. 28, 29, 32, and 33, bears N. 89° 09' W., 232.12 chs. dist., perpetuated by a rifle barrel, 12 ins. under ground, recorded in county court house as being restored from original BT, which is no longer in existence; from which locally established bearing trees as follows:

A prune tree, 13 ins. diam., bears N. 61½° E., 143 lks. dist., with scribe marks 8 CS BT. visible on bark.

A stump hole of prune tree, bears S. 25° E., 66 lks. dist.

A maple, 50 ins. diam., bears S. 45° W., 229 lks. dist., with scribe marks T29S S32 CS BT visible on opened blaze.

The cor. falls in garden plot where it is impractical to establish a permanent monument. Establish the following accessories:

An iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, bears N. 60° E., 56½ lks. dist., with brass cap marked T29S R5W S28 RM, 1957, with arrow pointing to the true corner.