

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS

34.43 Ravine, course SW.; asc. 136 ft. over S. slope.

38.77 Spur, slopes S. 60° W.; asc. 20 ft. over SW. slope.

39.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner,

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S R5W

S 26 | S 25
1957

from which

A fir, 17 ins. diam., bears S. 37 $\frac{1}{4}$ ° E., 38 lks. dist., marked $\frac{1}{4}$ S25 BT.A fir, 20 ins. diam., bears S. 87 $\frac{3}{4}$ ° W., 36 lks. dist., marked $\frac{1}{4}$ S26 BT.

Ascend 119 ft. over SW. slope.

50.78 Ridge, main divide between S. Myrtle Creek and Cedar Hollow Creek, bears E. and W.; desc. 213 ft. over N. slope.

59.61 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

N 1/16
S 26 | S 25
1957

from which

A fir, 18 ins. diam., bears N. 73 $\frac{1}{2}$ ° E., 63 lks. dist., marked N1/16 S25 BT.

A fir, 48 ins. diam., bears S. 78° W., 79 lks. dist., marked N1/16 S26 BT.

Descend 257 ft. over NE. slope.

72.23 South Myrtle Creek, 30 lks. wide, course N. 70° W.; asc. 12 ft. over right bank and enter open level field.

79.48 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 2 ins. diam., 12 ins. below the surface of the ground, with brass cap marked

T29S R5W
S 23 | S 24
S 26 | S 25
1957

from which

A cottonwood, 14 ins. diam., bears N. 19° E., 152 lks. dist., marked T29S R5W S24 BT.

A maple, 15 ins. diam., bears S. 88° E., 686 lks. dist., marked T29S R5W S25 BT.