

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS	
7.10	Dirt farm road, 15 lks. wide, bears N. 60° W. and S. 5° W.
11.72	Woven-wire fence, bears N. 10° W. and S. 10° E.
16.86	Power line, bears N. and S.
20.06	Point for the E 1/16 sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked $\begin{array}{r} \text{S } 24 \\ \text{E } 1/16 \text{ } \overline{\text{S } 25} \\ 1957 \end{array}$ from which A cottonwood, 9 ins. diam., bears S. 79½° W., 352 lks. dist., marked E 1/16 S25 BT. The corner falls in a large pasture, no other BTs. available.
24.54	Woven-wire fence, bears N. 20° W. and S. 20° E.
32.01	Woven-wire fence with 2 strands of barbed wire, bears N. 35° E. and S. 35° W.; leave farm lands.
32.86	Asphaltic highway, (S. Myrtle Creek Road) 32 lks. wide, bears N. 35° E. and S. 35° W.
33.59	Woven-wire fence with 2 strands of barbed-wire, bears N. 35° E. and S. 35° W.; enter scattering timber of logged area.
40.12	The ¼ sec. cor. of secs. 24 and 25 perpetuated by an iron rod, ¾ in. diam., 6 ins. above ground, firmly set. This cor. was restored from the original bearing trees, which are no longer in existence, Eppstein, County Surveyor, in 1938 and rehabilitated by Byron and Irving, Deputy County Surveyors, in 1953; from which the locally established bearing trees, as follows: A fir, 15 ins. diam., bears N. 58° E., 60½ lks. dist., marked with a partially healed blaze. A fir, 15 ins. diam., bears N. 85° W., 70½ lks. dist., with a partially healed blaze. A sawed cedar stump, 22 ins. diam., bears N. 6° W., 87 lks. dist., with CS visible on open blaze. A sawed fir stump, 18 ins. diam., bears N. 70° E., 63 lks. dist., with a healed blaze. At the corner point. Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked $\begin{array}{r} \text{T29S R5W} \\ \frac{1}{4} \text{ } \overline{\text{S } 24} \\ \text{S } 25 \\ 1957 \end{array}$ Deposit local corner material alongside the iron post.
	N. 89° 39' W., beginning new measurement.
	Ascend 6 ft. along S. slope., through logged area.
0.60	Spur, slopes S. 15° E.; desc. 6 ft. over SW. slope.