

Dependent Resurvey of Portion of Subdivisional Lines, T. 29 S., R. 5 W.

CHAINS

the original bearing trees, as follows:

A black oak, 16 ins. diam., bears N. 62½° E., 44 lks. dist., with healed blaze. (Record bearing N. 63° E.)

A black oak, 28 ins. diam., bears S. 74½° W., 34 lks. dist., with a healed blaze. (Record bearing N. 85° W.)

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

Fd. by G. DEC. 1981
BC. GRUBB RM 3-52

T29S R5W

S 23 | S 24

1957

from which

A fir, 17 ins. diam., bears S. 25° E., 46 lks. dist., marked ¼ S24 BT.

A fir, 15 ins. diam., bears S. 87° W., 78 lks. dist., marked ¼ S23 BT.

The cor. falls at the intersection of fences extending N., S., E., and W.

From this point a locally established cor. bears N. 17½° W., 3½ lks. dist., monumented with an iron post, ½ in. diam., 6 ins. above ground, firmly set.

Survey of Portion of Subdivisional Lines of sec. 25, T. 29 S., R. 5 W., Will. Mer., Oregon.


From the ¼ sec. cor. of secs. 25 and 36.

N. 0° 09' W., on the N. and S. center line of sec. 25.

Descend 82 ft. over NW. slope, through scattering timber of logged area and scattering undergrowth.

- 5.15 Head of ravine, course W.; asc. 25 ft. over SW. slope.
- 10.44 Top of ascent, slopes W.; desc. 20 ft. over NW. slope.
- 11.58 Ravine, course W.; asc. 172 ft. over SW. slope changing to S. slope.
- 17.30 Spur, slopes SW.; asc. 25 ft. along W. slope.
- 19.925 Point for the center S 1/16 sec. cor. of sec. 25.

Set and iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 9 ins. diam., bears S. 57¾° E., 33 lks. dist., marked CS1/16 S25 BT.

A fir, 12 ins. diam., bears S. 30° W., 52 lks. dist., mkd. (same.)