

Survey of Portion of Subdivisional Lines of Sec. 25, T. 29 S., R. 5 W.

CHAINS	<p>Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">NE 1/16 S 25</p> <p style="text-align: center;">1957</p> <p>from which</p> <p>A fir, 8 ins. diam., bears N. 66<math>\frac{1}{4}</math>° E., 93<math>\frac{1}{2}</math> lks. dist., marked NE 1/16 S25 BT.</p> <p>A fir, 20 ins. diam., bears S. 75<math>\frac{1}{2}</math>° W., 204 lks. dist., marked NE 1/16 S25 BT.</p> <p>Desc. 154 ft. over steep N. slope.</p>
25.67	S. Myrtle Creek, 30 lks. wide, course SW.; enter pasture land and asc. 69 ft. over general S. slope.
39.06	The E 1/16 sec. cor. of secs. 24 and 25.
	—————
	From the N 1/16 sec. cor. of secs. 25 and 30.
	S. 89° 41' W., on the E. and W. center line of the NE. $\frac{1}{4}$ of sec. 25.
	Descend 84 ft. over NW. slope of slide area through scattering timber and undergrowth.
2.51	Ravine, course N.; asc. 107 ft. over NE. slope.
5.35	Top of ascent, slopes N.; desc. 164 ft. along N. slope.
19.93	The NE 1/16 sec. cor. of sec. 25 and intersection with the N. and S. center line of the NE. $\frac{1}{4}$ of sec. 25.
	Descend 136 ft. along steep, broken N. slope.
29.58	Foot of descent, slopes N.; asc. 4 ft. over NE. slope.
30.98	Top of ascent, slopes N.; desc. 22 ft. over NW. slope.
31.76	Abandoned logging road, 15 lks. wide, bears NE. and SW., enter field.
38.12	Left bank of S. Myrtle Creek, course S. 30° W.
38.43	Right bank of S. Myrtle Creek; asc. 8 ft. over SE. slope.
39.06	Woven-wire fence, bears NE. and SW.
39.96	The center N 1/16 sec. cor. of sec. 25.
	From the center W 1/16 sec. cor. of sec. 25.
	N. 0° 30' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 25.
	Descend 408 ft. over N. slope, through heavy timber and dense undergrowth.
9.70	Ravine, course NE.; desc. 142 ft. over broken N. slope.
19.71	Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 25.
	Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked
	NW 1/16 S 25
	1957
	from which