

# County Surveyor's Record, Douglas County, Oregon

12130

1

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 1 W.  
Executed by Hans W. Thielsen, Cartographer  
Under Special Instructions dated August 3, 1955.

CHAINS

(Restoring the 1883 survey of Rufus S. Moore)

Beginning at the cor. of secs. 14, 15, 22 and 23, determined at record bearing and distance from the remains of the original SE. and NW. bearing trees:

A fir stump, 28 ins. diam., bears S. 72° E., 10 lks. dist., marked with the lower part of a blaze.

A fir stump, 14 ins. diam., bears N. 47° W., 31 lks. dist., marked with the lower part of a blaze. The sawed off tree lies downhill, 108 lks. dist., marked T32S R1W S15 BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T32S R1W	
S 15	S 14
S 22	S 23
1955	

from which new bearing trees

A fir, 15 ins. diam., bears N. 48° E., 89 lks. dist., marked T32S R1W S14 BT.

A fir, 23 ins. diam., bears S. 83 $\frac{1}{2}$ ° E., 51 lks. dist., marked T32S R1W S23 BT.

A fir, 30 ins. diam., bears S. 62 $\frac{1}{4}$ ° W., 137 lks. dist., marked T32S R1W S22 BT.

A fir, 30 ins. diam., bears N. 35° W., 90 lks. dist., marked **T32S R1W S 15 BT.**

N. 0° 12' W., bet. secs. 14 and 15.

Ascend 186 ft. along broken E. slope, through timber and undergrowth.

13.77 Slope changes to SE. slope.

18.74 Top of Umpqua Divide, bears N. 65° E. and S. 65° W.; desc. 152 ft. over broken NW. slope.

40.02 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

$\frac{1}{4}$	
S 15	S 14
1955	

from which

A red fir, 30 ins. diam., bears S. 44 $\frac{1}{2}$ ° E., 74 lks. dist., marked  $\frac{1}{4}$  S14 BT.

A white fir, 12 ins. diam., bears S. 47° W., 97 lks. dist., marked  $\frac{1}{4}$  S 15 BT.

Ascend 9 ft. over SW. slope.

41.94 Spur, slopes W.; desc. 638 ft. over NE. slope, changing to NW. slope.

80.04 The cor. of secs. 10, 11, 14 and 15, monumented with a weathered basalt stone, 12x8x6 ins., firmly set, with no remaining marks; from which the remains of the original NE. and SE. bearing trees: