

Dependent Resurvey, Portion of Subdivisional Lines of T. 32 S., R. 1 W.

CHAINS

A stump hole, bears N. 76° E., 14 lks. dist.

A rotted fir stump, bears S. 66° E., 13 lks. dist.  
with no remaining marks.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground  
with brass cap marked

T32S R1W  
S 10 | S 11  
S 15 | S 14  
1955

from which new bearing trees

A fir, 20 ins. diam., bears N. 83½° E., 80 lks. dist.  
marked T32S R1W S11 BT.

A hemlock, 24 ins. diam., bears S. 41° E., 53 lks. dist.  
marked T32S R1W S14 BT.

A hemlock, 12 ins. diam., bears S. 74½° W., 97 lks. dist.  
marked T32S R1W S15 BT.

A fir, 16 ins. diam., bears N. 4½° W., 81 lks. dist.,  
marked T32S R1W S10 BT.

Deposit basalt stone alongside the iron post.

Land, mountainous. Soil, rocky clay. Timber, fir, maple, and ce-  
dar; undergrowth, vine maple, arrowwood, huckleberry, and hazel.

N. 3° 48' E., bet. secs. 10 and 11.

Descend 231 ft. over NW. slope, through timber and undergrowth.

13.31 Logging road on curve, 20 lks. wide, bears W. and NW.; asc. 289 ft.  
over SW. slope.

27.53 Logging road, bears N. 60° W., and E.; asc. 4 ft. over SW. slope.

28.13 Spur ridge, bears NW. and E.; desc. 132 ft. over broken NE. slope.

38.33 The ¼ sec. cor. of secs. 10 and 11, determined at record bearing  
distance from the original bearing trees:

A fir, 18 ins. diam., bears East, 13 lks. dist., with  
marks BT uncovered.

A partially rotted fir stump, bears N. 62° W., 23 lks. dist.,  
with no remaining marks.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground,  
with brass cap marked

¼  
S 10 | S 11  
1955

from which new bearing trees

A red fir, 18 ins. diam., bears S. 8½° E., 26 lks. dist.,  
marked ¼ S11 BT.

A red fir, 14 ins. diam., bears S. 72½° W., 26 lks. dist.,  
marked ¼ S10 BT.