

Dependent Resurvey, Portion of Subdivisional Lines of T. 32 S., R. 1 W.

CHAINS

N. 1° 44' W., beginning new measurement.

Descend 43 ft. over NW. slope.

0.66 Ravine, drains N. 80° W.; descend 17 ft. along west slope.

11.15 Ravine, drains S. 40° W., ascend 269 ft. over SW. slope.

26.20 Spur ridge, bears N. 35° W.; and S. 30° E.; descend 373 ft. over NE. slope.

39.46 The cor. of secs. 2, 3, 10 and 11, determined at record bearing and distance from the original bearing trees:

A fir, 45 ins. diam., bears N. 68° E., 58 lks. dist., marked with a healed blaze.

A fir stump, 35 ins. diam., bears S. 60° E., 12 lks. dist., with no remaining marks.

A fir, 50 ins. diam., bears S. 75° W., 17 lks. dist., marked with a healed blaze.

A fir, 44 ins. diam., bears N. 50° W., 35 lks. dist., with marks S3 uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T32S R1W
S 3 | S 2
S 10 | S 11
1955

from which new bearing trees

A fir, 37 ins. diam., bears N. 89° E., 106 lks. dist., marked T32S R1W S2 BT.

A fir, 37 ins. diam., bears S. 36° E., 77 lks. dist., marked T32S R1W S11 BT.

A fir, 40 ins. diam., bears S. 32½° W., 377 lks. dist., marked T32S R1W S10 BT.

A fir, 23 ins. diam., bears N. 73¼° W., 127 lks. dist., marked T32S R1W S3 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, maple, and cedar undergrowth, vine maple, arrowwood, huckleberry, and hazel.

From the cor. of secs. 14, 15, 22 and 23.

N. 80° 59' W., bet. secs. 15 and 22.

Ascend 409 ft. over E. slope, through timber and undergrowth.

12.42 Top of Umpqua Divide, bears N. and S.; desc. 181 ft. over SW. slope.

32.82 Spur, slopes S. 30° W.; desc. 258 ft. over NW. slope.

35.30 Road on divide, bears N. 10° E. and S. 20° W.

40.33 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 24 ins. in the ground