

Dependent Resurvey, Portion of Subdivisional Lines of T. 32 S., R. 1 W.

CHAINS

to solid rock, and in a mound of stone to top, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 15 \\ S 22 \end{array}$$

1955

from which

A red fir, 50 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 186 lks. dist.,
marked $\frac{1}{4}$ S 15 BT.

A white fir, 20 ins. diam., bears S. $39\frac{1}{4}^{\circ}$ E., 31 lks. dist.,
marked $\frac{1}{4}$ S22 BT.

Descend 439 ft. over NW. slope.

72.75 Branch, 2 lks. wide, course N. 50° W.; asc. 25 ft. over NE. slope.

80.66 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

$$\begin{array}{l} T32S R1W \\ S 16 | S 15 \\ S 21 | S 22 \\ 1955 \end{array}$$

From which

A fir, 13 ins. diam., bears N. $59\frac{3}{4}^{\circ}$ E., 37 lks. dist.,
marked T32S R1W S15 BT.

A fir, 23 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ E., 94 lks. dist.,
marked T32S R1W S22 BT.

A fir, 28 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 31 lks. dist.,
marked T32S R1W S21 BT.

A fir, 20 ins. diam., bears N. 19° W., 7 lks. dist.,
marked T32S R1W S16 BT.

From this point the cor. of secs. 21, 22, 27 and 28, bears S. 1°
 $17'$ W., 77.60 chs. dist., determined at record bearing and distance
from the original NE. bearing tree:

A fir, 36 ins. diam., bears N. 87° E., 617 lks. dist.,
marks S22 uncovered.

At the corner point

Set an iron post, 36 ins. long., 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{l} T32S R1W \\ S 21 | S 22 \\ S 28 | S 27 \\ 1955 \end{array}$$

from which new bearing trees

A fir, 30 ins. diam., bears N. $38\frac{1}{4}^{\circ}$ E., 519 lks. dist.,
marked T32S R1W S22 BT.

A fir, 30 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E., 434 lks. dist.,
marked T32S R1W S27 BT.