

County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey, Portion of Subdivisional Lines of T. 32 S., R. 1 W.

CHAINS

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, and maple; undergrowth, vine, maple, arrowwood, huckleberry, and hazel.

From the cor. of secs. 10, 11, 14 and 15.

N. 82° 08' W., bet. secs. 10 and 15.

Descend 27 ft. over W. slope, through timber and undergrowth.

1.68 Branch, 3 lks. wide, course N.; ascend 11 ft. over NE. slope.

9.61 Top of ascent on N. slope; descend 289 ft. over NW. slope.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 24 ins. in the ground to solid rock and in a mound of stone to top, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 10 \\ S 15 \\ 1955 \end{array}$$

from which

A fir, 50 ins. diam., bears S. 13 $\frac{1}{2}$ ° W., 47 lks. dist., marked $\frac{1}{4}$ S15 BT.

A fir, 14 ins. diam., bears N. 48° W., 110 lks. dist., marked $\frac{1}{4}$ S10 BT.

Descend 227 ft. over SW. slope.

48.97 Branch, 5 lks. wide, course N. 40° W.; desc. 149 ft. over NW. slope.

66.11 Branch, 6 lks. wide, course N. 20° E.; asc. 475 ft. over E. slope.

79.86 The cor. of secs. 9, 10, 15 and 16.

Land, mountainous. Soil, rocky clay. Timber, scattering second growth fir and maple; undergrowth, vine maple, arrowwood, huckleberry, and hazel.

N. 1° 53' E., bet. secs. 9 and 10.

Descend 569 ft. over NE. slope, through timber and undergrowth.

21.16 Ravine, drains NE.; descend 180 ft. over NE. slope, changing to north slope.

30.78 Branch, 3 lks. wide, course NW.; ascend 51 ft. over NW. slope.

32.94 Top of ascent on west slope; descend 12 ft. over NW. slope.

35.94 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, determined at record bearing and distance from the original bearing trees:

A yew, 18 ins. diam., bears N. 75° E., 20 lks. dist., with marks $\frac{1}{4}$ S BT, uncovered.

A fir, 14 ins. diam., bears S. 43° W., 18 lks. dist., with marks BT uncovered.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked