

## Dependent Resurvey, Portion of Subdivisional Lines of T. 32 S., R. 1 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ S\ 9\ \frac{1}{4} | S\ 10 \\ 1955 \end{array}$$

from which new bearing trees

A yew, 8 ins. diam., bears S. 47° E., 41 lks. dist.,  
marked  $\frac{1}{4}$  S10 BT.

A fir, 8 ins. diam., bears S. 35 $\frac{1}{2}$ ° W., 30 lks. dist.,  
marked  $\frac{1}{4}$  S BT.

N. 0° 27' E., beginning new measurement.

Descend 30 ft. over NW. slope.

- 9.62 Stream, 10 lks. wide, course NW.; ascend 41 ft. over SW. slope.
- 14.00 Logging road, 30 lks. wide, bears NE. and SW.; descend 210 ft. over NW. slope.
- 25.30 Branch, 8 lks. course NE.; ascend 79 ft. over SE. slope.
- 27.54 Spur, slopes east; descend 32 ft. over NE. slope.
- 32.65 Bottom of descent on east slope; ascend 93 ft. over SE. slope.
- 38.46 Spur, slopes N. 70° E.; descend 5 ft. over NE. slope.
- 39.26 The cor. of secs. 3, 4, 9 and 10, determined at record bearing and distance from the original bearing trees:
- A fir, 10 ins. diam., bears N. 60° E., 10 lks. dist.,  
marks W S3 uncovered.
- A fir, 16 ins. diam., bears S. 73° E., 4 lks. dist.,  
marks 10 uncovered.
- A fir, 8 ins. diam., bears S. 35° W., 5 lks. dist.,  
marked with a healed blaze.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground,  
with brass cap marked

$$\begin{array}{c} T32S\ R1W \\ S4 | S\ 8 \\ \hline S9 | S\ 10 \\ 1955 \end{array}$$

from which new bearing trees

A fir, 8 ins. diam., bears N. 78° E., 45 lks. dist.,  
marked T32S R1W S3 BT.

A chinquapin, 8 ins. diam., bears S. 35 $\frac{1}{2}$ ° E., 55 lks. dist.,  
marked T32S R1W S10 BT.

A fir, 21 ins. diam., bears S. 82 $\frac{1}{4}$ ° W., 95 lks. dist.,  
marked T32S R1W S9 BT.

A fir, 30 ins. diam., bears N. 21° W., 31 lks. dist.,  
marked T32S R1W S4 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, maple and cedar;  
undergrowth, vine maple, arrowwood, huckleberry and hazel.