

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Line bet. Secs. 7 and 18, T. 25 S., R. 1 W.

CHAINS

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T25S RLW

$\frac{1}{4} \frac{S 7}{S 18}$

1957

from which

A fir, 30 ins. diam., bears N. 1° E., 39 lks. dist., marked $\frac{1}{4}$ S7 BT.

A hemlock, 7 ins. diam., bears S. 39½° W., 133 lks. dist., marked $\frac{1}{4}$ S18 BT.

Descend 76 ft. along N. slope.

- 44.80 Foot of descent, slopes N.; ascend 128 ft. along N. slope.
- 50.08 Spur, slopes NW.; descend 312 ft. over steep W. slope.
- 57.56 Spring branch, 2 lks. wide, course NW.; ascend 22 ft. along N. slope.
- 58.08 Point for the cor. of lots.1, 2, 19 and 20.

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap marked

$\frac{S 7}{L 19 | L 20}$

$\frac{L 2 | L 1}{S 18}$

S 18

1957

Ascend 41 ft. along steep N. slope.

- 61.30 Spur, slopes NW.; descend 501 ft. over W. slope.
- 73.20 Branch, 2 lks. wide, course NW.; descend 55 ft. along N. slope.
- 77.44 Point for the cor. of lots.2, 3, 18 and 19.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap marked

$\frac{S 7}{L 18 | L 19}$

$\frac{L 3 | L 2}{S 18}$

S 18

1957

Descend 147 ft. along N. slope changing to NW. slope.

- 82.37 North Fork of the East Fork of Rock Creek, 40 lks. wide, 1 ft. deep, course S. 50° W.; ascend 300 ft. over SE. slope.
- 83.14 Gravelled access road, 35 lks. wide, bears N. 10° E. and S. 10° W.
- 93.50 Spring seepage, course SE.; ascend 60 ft. over SE. slope.
- 96.80 A maple post, 3 ins. square, protruding 36 ins. above ground, firmly set, in a mound of stone, 3 ft. base, 1 ft. high, marked lot cor. lots 3, 4, 17 and 18; ascend 30 ft. along rocky S. slope.
- 104.00 Spring branch, 1 lk. wide, course SE.; ascend 411 ft. over E. slope.
- 116.16 Point for the cor. of lots 4, 5, 16 and 17.