

County Surveyor's Record, Douglas County, Oregon

1
 Dependent Resurvey of Portion of the East Bdy. of T. 29 S., R. 7 W.
 Executed by Hans W. Thielsen, Cadastral Surveyor
 Under Special Instructions dated March 29, 1957.

CHAINS

(Restoring the 1854 Survey by Nathaniel Ford.)

Beginning at the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of T. 29 S., R. 7 W., which is determined at record bearing and distance from trees apparently marked but not recorded by Campbell in 1910, accepted and recorded by Mensch in 1924, as follows:


A sawed fir stump, 28 ins. diam., bears S. $15\frac{1}{2}^\circ$ E., 26 lks. dist., plainly blazed and healed.

A fir, 20 ins. diam., bears S. $44\frac{1}{2}^\circ$ W., 27 lks. dist., marked T29S R7W S24 BT on partly healed blaze.

A fir, 11 ins. diam., bears N. 52° W., 12 lks. dist., marked T29S R7W S13 BT on partly overgrown blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



Pd. OK 8/87
 H. Johnston
 M101-60

from which new bearing trees,

A fir, 21 ins. diam., bears N. 45° E., 72 lks. dist., marked T29S R6W S18 BT.

A madrona, 17 ins. diam., bears S. 82° E., 94 lks. dist., marked T29S R6W S19 BT.

A fir, 8 ins. diam., bears N. 47° W., 139 lks. dist., marked T29S R7W S13 BT.


N. $1^\circ 38'$ W., bet. secs. 13 and 18, marking and blazing the true line.

Descend 310 ft. over N. slope through heavy timber and dense undergrowth.

9.40 Porter Creek, 5 lks. wide, course N. 80° E.; ascend 690 ft. over SE. slope.

38.36 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 17 ins. diam., bears S. 6° E., 72 lks. dist., mkd. $\frac{1}{4}$ S18 BT.

A fir, 12 ins. diam., bears N. $35\frac{1}{4}^\circ$ W., 90 lks. dist., marked $\frac{1}{4}$ S13 BT.

Ascend 170 ft. over SE. slope.

47.00 Ridge, bears NE. and SW.; descend 800 ft. over NW. slope.

76.30 Branch, 3 lks. wide, course NW.; ascend 15 ft. over SW. slope.