

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 29 S., R. 7 W.

CHAINS

(Restoring the 1854 survey by Nathaniel Ford)

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp. N. 88° 02' W., bet. secs. 13 and 24, marking and blazing the true line.

Descend 223 ft. along broken N. slope, changing to NW. slope, through heavy timber and dense undergrowth.

19.00 Porter Creek, 5 lks. wide, course NE.; asc. 644 ft. over E. slope.

43.84 The $\frac{1}{4}$ sec. cor. of sec. 13, only, determined at record bearing and distance from the remaining bearing tree marked by Campbell in 1910 as follows:

A fir snag, 14 ins. diam., bears N. 14° E., 70 lks. dist., marked $\frac{1}{4}$ S13 BT on partly healed blaze.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

T29S R7W

$\frac{1}{4}$ S 13

1957

from which new bearing trees,

A cedar, 5 ins. diam., bears N. 19° E., 149 lks. dist., marked $\frac{1}{4}$ S13 BT.

A cedar, 7 ins. diam., bears N. 14° W., 118 lks. dist., marked $\frac{1}{4}$ S13 BT.

N. 88° 02' W., beginning new measurement.

Ascend 59 ft. over E. slope.

4.80 Ridge, bears N. and S.; desc. 351 ft. over NW. slope.

24.10 Ravine, drains N.; ascend 377 ft. over NE. slope.

44.37 The cor. of secs. 13, 14, 23 and 24, determined at record bearing and distance from the remaining bearing trees marked by Campbell in 1910 as follows:

An uprooted fir, 36 ins. diam., plainly blazed and healed, the stump hole of which bears S. 67 $\frac{1}{2}$ ° E., 46 lks. dist.

A sawed fir stump, 36 ins. diam., bears S. 73° W., 28 lks. dist., marked T29S R7W S23 BT on opened blaze.

A fir, 36 ins. diam., bears N. 13° W., 52 lks. dist., with no marks visible on opened blaze.

and a bearing tree marked by Mensch in 1924:

A decayed fir stump, 30 ins. diam., bears N. 33° E., 68 lks. dist., marked T29S R7W S13 BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked