

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 7 W.

CHAINS

*FWD. OK  
4/11/11 M113-6*

T29S R7W  
S14 | S 13  
S 23 | S 24  
1957

*Fd. OK  
8/8/89  
H. Johnson  
M101-60*

from which new bearing trees,

A fir, 20 ins. diam., bears N. 73° E., 167 lks. dist., marked T29S R7W S13 BT.

A fir, 30 ins. diam., bears S. 45° E., 124 lks. dist., marked T29S R7W S24 BT.

A fir, 17 ins. diam., bears S. 14° W., 138 lks. dist., marked T29S R7W S23 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, maple, madrona and alder. Undergrowth, vine maple, hazel, arrowwood, Oregon grape and fern.

N. 0° 10' W., bet. secs. 13 and 14.

Descend 715 ft. over NE. slope through heavy timber and dense undergrowth.

24.60 Kent Creek, 5 lks. wide, course N. 75° E., asc. 380 ft. over S. slope.

30.15 Graded road, 20 lks. wide, bears E. and W.

39.34 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

T29S R7W  
1/4  
S 14 | S 13  
1957

from which

A fir, 8 ins. diam., bears S. 38° E., 53 lks. dist., mkd. 1/4 S13 BT.

A fir, 14 ins. diam., bears N. 72° W., 108 lks. dist., marked 1/4 S14 BT.

Ascend 170 ft. over S. slope.

46.50 Spur, slopes S. 70° E.; descend 240 ft. over NE. slope.

53.40 Ravine, drains S. 70° E.; ascend 540 ft. over SE. slope.

73.50 Ridge, bears E. and W.; descend 140 ft. over NE. slope.

78.68 Point for cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S R7W  
S 11 | S 12  
S 14 | S 13  
1957

from which