

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the Subdivisional Lines of T. 29 S., R. 7 W.

CHAINS

Descend 30 ft. over SW. slope through heavy timber and dense undergrowth.

2.85 Branch, 2 lks. wide, course SE.; ascend 240 ft. over E. slope.

14.20 Spur, slopes S. 10° W.; descend 80 ft. over SW. slope.

18.40 Ravine, drains S.; ascend 250 ft. over SE. slope.

27.60 Graded road, bears N. and S.

33.50 Spur, slopes S.; thence along S. slope.

34.00 Ridge, bears N. 80° E. and S. 80° W.; descend 50 ft. over NW. slope.

38.16 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. 1 in. diam., 18 ins. in the ground to solid rock, and in a mound of earth and stone to top, with brass cap marked

T29S R7W

$\frac{1}{4}$ S 15
S 22
1957

from which

A fir, 13 ins. diam., bears N. 16° E., 96 lks. dist.,
 $\frac{1}{4}$ S15 BT.

A fir, 23 ins. diam., bears S. 53° W., 150 lks. dist.,
 $\frac{1}{4}$ S22 BT.

Descend 470 ft. over NW. slope.

58.00 Ravine, drains N.; ascend 100 ft. over NE. slope.

64.00 Spur, slopes N.; descend 130 ft. over broken NW. slope, changing to N. slope.

76.32 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T29S R7W
S 16 | S 15
S 21 | S 22
1957

from which

A fir, 59 ins. diam., bears N. 45° E., 88 lks. dist.,
marked T29S R7W S15 BT.

A fir, 18 ins. diam., bears S. 61° E., 46 lks. dist.,
marked T29S R7W S22 BT.

A fir, 28 ins. diam., bears S. 39° W., 31 lks. dist.,
marked T29S R7W S21 BT.

A fir, 30 ins. diam., bears N. 47° W., 21 lks. dist.,
marked T29S R7W S16 BT.

From this point the cor. of secs. 27, 28, 33 and 34 bears S. 0° 06'E., 159.64 chs. dist., determined from each of the original bearing trees and trees marked by Mensch in 1924. The iron post set by Mensch is gone.

At the corner point