

County Surveyor's Record, Douglas County, Oregon

1

Homestead Entry Survey No. 178, T. 26 S., R. 2 E.
 Executed by Fredrick W. Rase, Surveyor
 Under Special Instructions dated December 17, 1915.

CHAINS

Entryman: John B. Wright. H.E. No. 09413, dated March 31, 1914.
 Land District: Roseburg, Oregon.

TIE LINE.

August 23, 1916:- Preliminary to the survey of this homestead entry, I make the following connection: from cor. No. 1 of this survey, hereinafter described, I run by traverse,
 N. 53° 00' E., 30.00 chs.

N. 52° 16' E., 1.34 chs. to U.S.L.M. No. 142, (described in field notes of HES No. 93.) The true bearing and length of this line from cor. No. 1 is N. 52° 59' E., 31.34 chs., as determined by calculation.

(Note by transcriber: Ties to H.E.S. No. 178 are given in the field notes of the survey of subdivisional lines of T. 26 S., R. 2 E.)

All listing cors. referred to herein are properly identified, being mkd. and witnessed as described by the Forest Service in the listing survey.

August 23, 1916: I begin at cor. No. 1 of this survey, identical with cor. No. 7 of listing survey, a pine tree 30 ins. diam. I destroy all listing survey marks and mark the tree 1 HES 178 on side facing claim, from which

An oak, 14 ins. diam., bears S. 39° 40' W., 53 lks. dist., mkd. X 1 HES 178 BT.

A fir, 14 ins. diam., bears N. 38° 16' W., 49 lks. dist., mkd. X 1 HES 178 BT.
 raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

U.S.L.M. No. 142 bears N. 52° 59' E., 31.34 chs. dist.
 Cor. No. 4 of H.E.S. No. 142 (accepted) bears N. 8° 45' E., 13.47 chs. dist. (direct measurement)

Thence I run, S. 45° 00' W., on a random line and at 15.25 chs. fall 25.3 lks. N. 45° 00' W. of cor. No. 1 of listing survey. (The true bearing and length of this line is S. 44° 03' W., 15.25 chs.)

Returning to Cor. No. 1 of this survey, above described, I run

S. 44° 03' W., on a true line, along west bdy. of Illihee Ranger Station, through scattering fir and oak timber, over level land.

10.62 Trail, bears east and west.

12.10 Trail, bears east and west.

15.25 Cor. No. 2, identical with cor. No. 1 of listing survey and southwest cor. of Illihee Ranger Station, which I destroy and in its place Set a lava stone, 26x12x10 ins., 16 ins. in the ground, over a stone mkd. with a cross for cor. No. 2 of this survey, mkd. 2 HES 178 on side facing the claim, from which

A pine, 8 ins. diam., bears S. 44° 45' E., 117 lks. dist., marked X 2 HES 178 BT.

A pine, 12 ins. diam., bears N. 21° 15' E., 243 lks. dist., marked X 2 HES 178 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

Thence I run, S. 8° 00' E. on a random line, and at 9.92 chs. fall 6 lks. N. 82° 00' E. of cor. No. 2 of listing survey.

NOTE: SEE C.S. 63/5 FOR
 COPY OF "LISTING SURVEY"
 NOTES.