

County Surveyor's Record, Douglas County, Oregon

Homestead Entry Survey No. 178, T. 26 S., R. 2 E.

CHAINS

(The true bearing and length of this line is S. 7° 39' E., 9.92 chs.)

Returning to cor. No. 2 of this survey, above described, I run S. 7° 39' E., on a true line. Over level land.

6.00 Leave flat; descend southeast slope, through scattering fir and pine timber and undergrowth.

9.92 Cor. No. 3 (60 ft. below flat) identical with cor. No. 2 of listing survey, which I destroy, and in its place

Set a lava stone, 30x9x9 ins., 20 ins. in the ground, over a stone mkd. with a cross for cor. No. 3 of this survey, mkd. 3 HES 178 on side facing the claim; from which

A fir, 14 ins. diam. bears N. 83° 15' E., 117 lks. dist., mkd. X 3 HES 178 BT.

A pine, 40 ins. diam., bears S. 27° 45' W., 90 lks. dist., mkd. X 3 HES 178 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Thence I run N. 74° 34' W. on a true line.

Gradual ascent of southeast slope, through scattering fir and pine timber.

2.50 Top of ascent, 60 ft. above cor. No. 3; thence along southerly edge of flat.

46.27 Cor. No. 4, identical with cor. No. 3 of listing survey, which I destroy and in its place

Set a lava stone, 24x10x8 ins., 14 ins. in the ground, over a stone mkd. with a cross for cor. No. 4 of this survey, mkd. 4 HES 178 on side facing the claim; from which

An oak, 14 ins. diam., bears N. 74° 00' W., 128 lks. dist., marked X 4 HES 178 BT.

A pine, 14 ins. diam., bears N. 75° 15' E., 23 lks. dist., marked X 4 HES 178 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Thence I run, N. 7° 57' E. on a true line, (objective cor. in sight.) Over flat, through scattering pine, oak, and fir timber.

11.86 Cor. No. 5, identical with cor. No. 4 of listing survey, which I destroy and in its place

Set a granite stone 26x15x10 ins., 16 ins. in the ground, over a stone mkd. with a cross for cor. No. 5 of this survey, mkd. 5 HES 178 on side facing the claim; from which

A pine, 40 ins. diam., bears S. 29° 30' W., 41 lks. dist., marked X 5 HES 178 BT.

A tamarack, 24 ins. diam., bears N. 46° 45' E., 100 lks. dist., marked X HES 5 178 B T.

Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Cor. No. 2 of H.E.S. No. 93 (accepted) bears N. 75° 57' W., 34.60 chs. dist. (direct measurement.)