

County Surveyor's Record, Douglas County, Oregon

1

Homestead Entry Survey No. 182, T. 26 S., R. 2 E.
 Executed by Fredrick W. Rase, Surveyor
 Under Special Instructions dated January 7, 1916

CHAINS

Entryman: Burley O. Wright, Glide, Oregon. H.E. 09518, Roseburg, Oregon.

August 25, 1916: I begin at cor. No. 1 of this survey, identical with cor. No. 1 of listing survey and Forest Service Monument, which is a Douglas fir tree 36 ins. diam. I obliterate all listing survey marks and mark the tree 1 HES 182 on side facing the claim, from which

A pine, 42 ins. diam., bears N. 3° 15' W., 152 lks. dist., marked X 1 HES 182 BT.

A pine, 32 ins. diam., bears N. 13° 45' E., 191 lks. dist., marked X 1 HES 182 BT.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

U.S.L.M. No. 142 bears S. 84° 25' E., 158.19 chs. dist., (described in field notes of H.E.S. No. 93.)

Cor. No. 5, H.E.S. No. 93, (accepted) bears N. 74° 30' E., 22.40 chs. dist. (direct measurement).

Cor. No. 5 of H.E.S. No. 178, surveyed by me, bears S. 68° 53' E., 85.95 chs. dist. (direct measurement).

Thence I run, West on a random line, and at 40.76 fall 63 lks. south of cor. No. 2 of listing survey. (The true bearing and length of this line is N. 89° 07' W., 40.76 chs.)

Returning to cor. No. 1 of this survey, above described, I run

N. 89° 07' W. on a true line.

Ascend southeast slope, through dense undergrowth.

3.80 Top of ascent, 50 ft. above cor.; trail bears northwest and southeast; thence over rolling land.

7.80 Draw, course south; ascend southeast slope of spur.

11.90 Top of spur, slopes south, 50 ft. above draw; descend southwest slope of ravine.

21.90 Bottom of ravine, course south, 200 ft. below top of spur; ascend southeast slope.

40.76 Cor. No. 2 (250 ft. above ravine) identical with cor. No. 2 of listing survey, which I destroy, and in its place Set a granite stone 24x13x10 ins., 14 ins. in the ground, over a stone mkd. with a cross for cor. No. 2 of this survey, mkd. 2 HES 182 on side facing the claim, from which

A fir, 36 ins. diam., bears S. 29° 20' W., 168 lks. dist., marked X 2 HES 182 BT.

No other bearings available. Pits impracticable. Raise a mound of stone 3 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

Lookout Mt. bears S. 64° W., approximately 6 miles dist.

Thence I run, North on a random line, and at 14.77 chs. fall 33 lks. west of cor. No. 3 of listing survey. (The true bearing and length of this line is N. 1° 17' E., 14.77 chs.)

Returning to cor. No. 2 of this survey, above described, I run

N. 1° 17' E. on a true line.

Ascend south slope, through dense undergrowth.