

Homestead Entry Survey No. 227, T. 26 S., R. 2 E.

CHAINS

- 14.25 Fence, bears east and west; enter cultivated field.
- 20.65 Fence, bears northeast and southwest; leave cultivated field.
Ascend steep south slope, 90 ft. above cor. No. 1.
- 42.79 To cor. No. 2 of H.E.S. No. 142, heretofore described, 135 ft. above point of ascent, also point for cor. No. 4 of listing survey, which I establish as cor. No. 2 of this survey as follows:
- Mark a fir tree, 28 ins. diam., 2 HES 227 on side facing the claim, for cor. No. 2 of this survey; from which
- A pine, 28 ins. diam., bears S. 18° 15' W., 45 lks. dist., marked X2HES 227 BT.
- A fir, 30 ins. diam., bears N. 89° 00' W., 76 lks. dist., marked X2HES 227 BT.
- Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.
-
- Thence I run S. 53° 15' E., on a random line, and at 10.76 chs. fall 124 lks. N. 36° 45' E. of cor. No. 3 of listing survey. (The true bearing and length of this line is S. 46° 41' E., 10.83 chs.)
- Returning to cor. No. 2 of this survey, above described, I run S. 46° 41' E., on a true line.
Descend south slope, through scattered pine and fir timber.
- 10.83 To cor. No. 3 of the listing survey, which I destroy and in its place establish cor. No. 3 of this survey, 160 ft. below cor. No. 2, as follows:
- Set a porphyry stone, 24x10x6 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 3 of this survey, marked 3 HES 227 on side facing the claim; from which
- A fir, 13 ins. diam., bears N. 3° 45' E., 37 lks. dist., marked X 3 HES 227 BT.
- A fir, 10 ins. diam., bears S. 79° 00' W., 33 lks. dist., marked X 3 HES 227 BT.
- Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.
-
- Thence I run S. 7° 00' W., on a random line, and at 28.00 chs. fall 46½ lks. S. 83° 00' E. of cor. No. 2 of listing survey. (The true bearing and length of this line is S. 7° 57' W., 28.00 chs.)
- Returning to cor. No. 3 of this survey, above described, I run S. 7° 57' W., on a true line, over rolling land, through pine and fir timber.
- 28.00 To cor. No. 2 of listing survey, which I destroy and in its place establish cor. No. 4 of this survey as follows:
- Set a sandstone, 26x8x6 ins., 16 ins. in the ground, over a stone marked with a cross for cor. No. 4 of this survey, marked 4 HES 227 on side facing the claim, from which
- A pine, 36 ins. diam., bears S. 83° 45' E., 29 lks. dist., marked X 4 HES 227 BT.
- A fir, 42 ins. diam., bears S. 37° 00' W., 76 lks. dist., marked X 4 HES 227 BT.
- Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist.,