

County Surveyor's Record, Douglas County, Oregon

12182

1

Homestead Entry Survey No. 229, Umpqua National Forest
 Executed by Geo. W. Root, Surveyor-Forest Service.
 Under Special Instructions dated March 17, 1917.

CHAINS

Entryman: Abraham Wilson. H.E. No.--Not yet entered. Land Office:
 Roseburg, Oregon.

H. E. S. No. 229.

All listing cors referred to herein are properly identified, being
 marked and witnessed as described by the Forest Service in the
 listing survey.

October 20, 1917: Beginning at point for cor. No. 1 of this survey,
 identical with cor. No. 4 of the listing survey, which I destroy
 and in its place establish cor. No. 1 of this survey as follows:
 Set a diorite stone, 24x12x12 ins., 14 ins. in the ground, over a
 stone marked with a cross for cor. No. 1 of this survey, marked
 1 HES 229 on side facing the claim, from which

A fir, 6 ins. diam., bears N. 66° 15' W., 63 lks. dist.,
 marked X 1 HES 229 BT.

A madrona, 6 ins. diam., bears N. 11° 00' E., 32 lks. dist.,
 marked X 1 HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on each course, 7 ft. dist.,
 and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft.
 dist., within the claim.

U.S.L.M. No. 142, described in field notes of H.E.S. No. 93,
 bears N. 74° 23' W., 98.97 chs. dist.

Thence I run S. 61° 00' E., on a random line, and at 38.06 chs. fall
 33 lks. N. 29° 00' E. of cor. No. 3 of listing survey. (The true
 bearing and length of this line is S. 60° 30' E., 38.06 chs.)

Returning to cor. No. 1 of this survey, above described, I run

S. 60° 30' E. on a true line, over level land, through open brush
 in burn, at top of steep descent to Copeland Creek and North Ump-
 qua River.

38.06 To cor. No. 3 of the listing survey, which I destroy and in its place
 establish cor. No. 2 of this survey as follows:

Set a diorite stone, 24x8x6 ins., 14 ins. in the ground, over a
 stone marked with a cross for cor. No. 2 of this survey, marked
 2 HES 229 on side facing the claim, from which

A fir, 16 ins. diam., bears N. 82° 00' E., 32 lks. dist.,
 marked X 2 HES 229 BT.

A fir, 16 ins. diam., bears N. 28° 00' E., 66 lks. dist.,
 marked X 2 HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on this and the succeeding
 course, 7 ft. dist., and raise a mound of earth, 4 ft. base,
 2 ft. high, 3½ ft. dist., within the claim.

Thence I run S. 15° 00' E., on a random line, and at 15.95 chs. fall
 4 lks. N. 75° 00' E. of cor. No. 2 of listing survey. (The true
 bearing and length of this line is S. 14° 51' E., 15.95 chs.)

Returning to cor. No. 2 of this survey, above described, I run

S. 14° 51' E., on a true line,
 Over level land; through open brush at top of steep descent to
 Copeland Creek.

12.10 Trail bears east and west; ascend through fir and pine timber.

15.95 To Cor. No. 2 of listing survey, 20 ft. above trail, which I now