

## Homestead Entry Survey No. 229, T. 26 S., R. 2 E.

## CHAINS

destroy and in its place establish cor. No. 3 of this survey as follows:

Set a diorite stone, 24x12x10 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 3 of this survey, marked 3 HES 229 on side facing the claim, from which

A fir, 14 ins. diam., bears S. 56° 15' E., 19 lks. dist., marked X 3 HES 229 BT.

A fir, 8 ins. diam., bears N. 26° 45' E., 23 lks. dist., marked X 3 HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

Thence I run S. 65° 00' W., on a random line, and at 26.89 chs. fall 33 lks. S. 25° 00' E. of cor. No. 1 of listing survey. (The true bearing and length of this line is S. 65° 42' W., 26.89 chs.)

Returning to Cor. No. 3 of this survey, above described, I run S. 65° 42' W., on a true line,  
Ascend through fir and pine timber.

3.80 Spur, slopes north, 60 ft. above cor. No. 2; descend.

14.40 Base of slope, 60 ft. below spur; cross level land, through dead fallen timber.

20.25 Creek, 2 lks. wide, course north; ascend gentle slope.

26.89 To Forest Service Monument and cor. No. 1 of the listing survey, 50 ft. above creek. I destroy marks of listing survey corner and Forest Service Monument and in its place establish cor. No. 4 of this survey as follows:

Mark a fir tree, 30 ins. diam., 4 HES 229 on side facing the claim for cor. No. 4 of this survey, from which

A fir, 28 ins. diam., bears S. 85° 30' E., 21 lks. dist., marked X 4 HES 229 BT.

A fir, 24 ins. diam., bears N. 39° 15' W., 167 lks. dist., marked X 4 HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

October 20, 1917.

October 21, 1917:--From cor. No. 4 of this survey, above described, I run S. 28° 00' E., on a random line, and at 10.89 chs. fall 13 lks. S. 62° 00' W. of the cor. No. 7 of listing survey. (The true bearing and length of this line is S. 28° 41' E., 10.89 chs.)

Returning to cor. No. 4 of this survey, above described, I run,

S. 28° 41' E., on a true line; descend gentle slope, through scattered timber and open brush.

8.90 Base of descent, 25 ft. below cor. No. 4; ascend through dense growth of small pine and fir timber.

10.89 To cor. No. 7 of listing survey, 20 ft. above point of ascent, which I now destroy and in its place establish cor. No. 5 of this survey as follows:

Set a diorite stone, 24x10x10 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 5 of this survey, marked