

Homestead Entry Survey No. 229, T. 26 S., R. 2 E.

CHAINS

5 HES 229 on side facing the claim, from which

A fir, 15 ins. diam., bears N. 51° 15' W., 9 lks. dist.,
marked X5HES 229 BT.

A fir, 12 ins. diam., bears N. 48° 30' E., 8 lks. dist.,
marked X5HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on this and the succeeding
course, 7 ft. dist., and raise a mound of earth, 4 ft. base,
2 ft. high, 3½ ft. dist., within the claim.

Thence I run West, on a random line, and at 8.89 chs. fall 15 lks.
south of cor. No. 6 of listing survey. (The true bearing and
length of this line is N. 89° 02' W., 8.89 chs.)

Returning to cor. No. 5 of this survey, above described, I run

N. 89° 02' W., on a true line,

Over level land, through dense undergrowth of small pine and fir
timber at south edge of opening.

8.89 To cor. No. 6 of listing survey, the marks of which I now destroy,
and in its place establish cor. No. 6 of this survey, as follows:
Mark a fir tree, 16 ins. diam., 6 HES 229 on side facing the claim,
for cor. No. 6 of this survey, from which

A fir, 16 ins. diam., bears N. 42° 15' W., 14 lks. dist.,
marked X 6 HES 229 BT.

A fir, 20 ins. diam., bears N. 85° 45' E., 13 lks. dist.,
marked X 6 HES 229 BT.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist.,
within the claim.

Thence I run N. 21° 00' W., on a random line, and at 36.31 chs. fall
295 lks. N. 69° 00' E. of cor. No. 5 of listing survey. (The true
bearing and length of this line is N. 25° 40' W., 36.31 chs.)

Returning to cor. No. 6 of this survey, above described, I run

N. 25° 40' W., on a true line,

Descend gentle slope, through old burn and scattered pine and fir
timber.

36.31 To cor. No. 5 of listing survey, 50 ft. below cor. No. 6 of this
survey. I destroy the listing corner and in its place establish
cor. No. 7 of this survey as follows:

Set a cinder stone, 24x12x6 ins., 14 ins. in the ground, over a
stone marked with a cross for cor. No. 7 of this survey, marked
7 HES 229 on side facing the claim, from which

A pine, 8 ins. diam., bears N. 66° 30' W., 56 lks. dist.,
marked X 7 HES 229 BT.

A pine, 7 ins. diam., bears S. 45° 45' W., 41 lks. dist.,
marked X 7 HES 229 BT.

Dig pits, 24x24x12 ins., crosswise on this and the succeeding
course, 7 ft. dist., and raise a mound of earth, 4 ft. base,
2 ft. high, 3½ ft. dist., within the claim.

Thence I run, N. 15° 00' E., on a random line, and at 22.85 chs.
fall 77 lks. N. 75° 00' W. of cor. No. 1 of listing survey. (The
true bearing and length of this line is N. 16° 56' E., 22.86 chs.)

Returning to cor. No. 7 of this survey, above described, I run,