

Resurvey of the North Boundary of T. 32 S., R. 9 W.

CHAINS

for cor. of secs. 3 and 4, with brass cap marked

S 4	S 3
T32S	R9W
1917	

from which

A fir, 20 ins. diam., bears S. 70° E., 44 lks. dist.,
marked T32S R9W S3 BT.

A fir, 20 ins. diam., bears S. 81° W., 84 lks. dist.,
marked T32S R9W S4 BT.

Land, mountainous. Soil, clay loam, stony in places, 2nd rate.
Timber, fir. Undergrowth, vine maple, live oak, hazel, huckle-
berry and fir.

N. 89° 50' W., resurveying N. bdy. of sec. 4.

Along S. slope, through heavy timber and dense undergrowth.

0.85 Creek, 1 lk. wide, course S.

4.15 Ravine, course S.

21.36 Intersect the cor. of secs. 33 and 34, which is a decayed post,
marked and witnessed as described by surveyor general. I perpet-
uate this cor., as follows: alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,
for cor. of secs. 33 and 34, T. 31 S., R. 9 W. only, with brass
cap marked

T31S	R9W
S 33	S 34
1917	

from which

A fir, 30 ins. diam., bears N. 8° E., 20 lks. dist.,
marked T31S R9W S34 BT. (Old B. T.)

A fir, 24 ins. diam., bears N. 20° W., 93 lks. dist.,
marked T31S R9W S33 BT. (Old B. T.)

Thence, N. 87° 41' W., continuing my measurements.

24.00 Begin descent of steep S. slope.

37.49 Intersect the old $\frac{1}{4}$ cor. of sec. 4 only, which is a yew tree, 20
ins. diam., marked and witnessed as described by the surveyor
general. I change this cor. to an angle point, destroying all
marks on the old cor. and marking AP on the N. side, from which

An alder, 14 ins. diam., bears S. 59° W., 50 lks. dist.,
marked AP BT. (Old B. T.)

An alder, 24 ins. diam., bears N. 56° W., 42 lks. dist.,
marked AP BT. (Old B. T.)

Thence S. 89° 02' W., continuing my measurements.

37.80 Walker Creek, 20 lks. wide, course N.; ascend steep NE. slope.

40.01 (40.00 chs. departure.)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 4 only, with brass cap marked

$\frac{1}{4}$ S 4
1917

from which