

## County Surveyor's Record, Douglas County, Oregon

7

## Resurvey of the North Boundary of T. 32 S., R. 9 W.

CHAINS

A fir, 40 ins. diam., bears S. 52° E., 58 lks. dist.,  
marked  $\frac{1}{4}$  S4 BT.

A fir, 60 ins. diam., bears S. 67° W., 13 lks. dist.,  
marked  $\frac{1}{4}$  S4 BT.

51.50 Top of spur, slopes SE.; along S. slope.

54.30 Ravine, course SE.; ascend.

61.34 Intersect the  $\frac{1}{4}$  cor. of sec. 33, which is a decayed post, firmly set,  
marked and witnessed as described by the surveyor general, with  
the exception that the S. bearing tree is 30 lks. dist. instead  
of 300 lks. dist., as given in the field notes. I perpetuate  
this cor. as follows: alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground,  
for  $\frac{1}{4}$  cor. of sec. 33, T. 31 S., R. 9 W. only, with brass cap  
marked

$\frac{1}{4}$  S33

1917

from which

A chinquapin, 20 ins. diam., bears N. 76° 30' E., 94 lks. dist.,  
marked  $\frac{1}{4}$  S33 BT. (Old B. T.)

A fir, 36 ins. diam., bears N. 25° W., 81 lks. dist.,  
marked  $\frac{1}{4}$  S33 BT. (New B. T.)

Thence West, continuing my measurements.

63.00 Top of spur, slopes N.; descend NW. slope.

71.00 Ravine, course NW.

76.06 Intersect the old cor. of secs. 4 and 5, which is a small wooden  
peg driven in the ground, not marked, witnessed as described by  
the surveyor general, except that the NW. tree has fallen and no  
marks were found on the NE. and SE. bearing trees. I change  
this cor. to an angle point and perpetuate it as follows: along-  
side the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,  
for angle point, with brass cap marked

A P

1917

from which

A chinquapin, 18 ins. diam., bears N. 45° E., 59 lks. dist.,  
marked AP BT. (Old B. T.)

A yew, 8 ins. diam., bears S. 27° W., 29 lks. dist.,  
marked AP BT. (Old B. T.)

Thence S. 88° 14' W., continuing my measurements.

80.01 (80.00 chs. departure)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,  
for cor. of secs. 4 and 5, with brass cap marked

S 5 | S 4  
T32S | R9W

1917

from which

A fir, 30 ins. diam., bears S. 56° E., 42 lks. dist.,  
marked T32S R9W S4 BT.

A fir, 40 ins. diam., bears S. 75° W., 41 lks. dist.,  
marked T32S R9W S5 BT.