

County Surveyor's Record, Douglas County, Oregon

10

Resurvey of the North Boundary of T. 32 S., R. 9 W.

CHAINS

N. 89° 16' W., resurveying N. bdy. of sec. 6.

Descend rocky NW. slope, through heavy timber and dense undergrowth.

1.00 Ravine, course NW.; ascend.

2.00 Top of rocky point, slopes NW.; descend.

10.25 Slide Creek, 20 lks. wide, course N.; ascend.

20.56 Intersect the cor. of secs. 31 and 32, which is a basalt stone, 16x10x5 ins., loosely set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 31 and 32, T. 31 S., R. 9 W., only, with brass cap marked

| | |
|------|------|
| T31S | R9W |
| S 31 | S 32 |

1917

from which

A yew, 8 ins. diam., bears N. 16° E., 38 lks. dist., marked T31S R9W S32 BT. (Old B. T.)

A yew, 8 ins. diam., bears N. 31° W., 47 lks. dist., marked T31S R9W S31 BT. (Old B. T.)

Thence S. 86° 25' W., continuing my measurements

Ascend steep rocky NE. slope.

32.56 Intersect the old $\frac{1}{4}$ cor. of sec. 6, which is a laurel tree, 6 ins. diam., marked and witnessed as described by the surveyor general. I change this cor. to an angle point, destroying all marks on the cor. and marking it A P on N. side, from which

A fir, 48 ins. diam., bears S. 15° E., 41 lks. dist., marked AP BT. (Old B. T.)

A fir, 40 ins. diam., bears N. 5° W., 42 lks. dist., marked AP BT. (Old B. T.)

Thence S. 89° 33' W., continuing my measurements

40.02 (40.00 chs. departure)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 6 only, with brass cap marked

| | |
|-------------------|--|
| $\frac{1}{4}$ S 6 | |
|-------------------|--|

1917

from which

A fir, 24 ins. diam., bears S. 37° E., 31 lks. dist., marked $\frac{1}{4}$ S6 BT.A fir, 24 ins. diam., bears S. 14° W., 26 lks. dist., marked $\frac{1}{4}$ S6 BT.

48.50 Leave heavy timber; enter low brush, bears N. and S.

51.00 Top of spur, slopes SE.; along S. slope.

59.63 Intersect the $\frac{1}{4}$ cor. of sec. 31, which is a basalt stone, 18x12x6 ins., loosely set, marked and witnessed as described by the surveyor general, both bearing trees now being dead. I perpetuate this cor., as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,