

County Surveyor's Record, Douglas County, Oregon

Resurvey of the North Boundary of T. 32 S., R. 9 W.

CHAINS

for $\frac{1}{4}$ cor. of sec. 31, T. 31 S., R. 9 W. only, with brass cap mkd.

$\frac{1}{4}$ S 31

1917

from which

A fir, 24 ins. diam., bears N. 78° 30' E., 57 lks. dist.,
marked $\frac{1}{4}$ S31 BT. (New B. T.)

A pinon, 10 ins. diam., bears N. 7° W., 207 lks. dist.,
marked $\frac{1}{4}$ S31 BT. (New B. T.)

Thence West, continuing my measurements.

62.00 Top of ridge, bears NE. and SW.; descend NW. slope.

65.80 Enter heavy timber, bears N. and S.

67.86 Intersect the closing cor. of Tps. 32 S., Rs. 9 and 10 W., which is a basalt stone, 18x16x7 ins., loosely set, marked and witnessed as described by the surveyor general. I perpetuate this cor. as follows: alongside the old cor.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for closing cor. of Tps. 32 S., Rs. 9 and 10 W., with brass cap marked

T31S R9W

S 31

S 1 | S 6

R10W | R9W

CC

T32S

1917

from which

A fir, 16 ins. diam., bears S. 24° E., 60 lks. dist.,
marked T32S R9W S6 CC BT. (Old B. T.)

A fir, 16 ins. diam., bears S. 23° W., 22 lks. dist.,
marked T32S R10W S1 CC BT. (Old B. T.)

Land, mountainous. Soil, stony clay loam and shale rock, 3rd and 4th rate. Timber, fir, sugar pine, yew and laurel. Undergrowth, live oak, tan oak and buckhorn.

Resurvey of 7th Standard Parallel South, through Range 9 West Executed by Fred Mensch and Gerald A. Sorrels, Surveyors Under Special Instructions, Group 35, dated December 22, 1916

From the standard cor. of Tps. 32 S., Rs. 8 and 9 W., which is a fir post, firmly set, marked and witnessed as described by the surveyor general, with the exception that the NE. bearing tree is now dead. I perpetuate this cor., as follows: alongside the old cor.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of Tps. 32 S., Rs. 8 and 9 W., with brass cap marked

S C

T32S

R9W | R8W

S 36 | S 31

1917

from which

A fir, 8 ins. diam., bears N. 32° E., 29 lks. dist.,
marked SC T32S R8W S31 BT. (New B. T.)

A fir, 14 ins. diam., bears N. 82° W., 16 lks. dist.,
marked SC T32S R9W S36 BT. (Old B. T.)

At this cor. the latitude is 42° 44' N., longitude 123° 43' W.,