

County Surveyor's Record, Douglas County, Oregon

Resurvey of 7th Standard Parallel South, through Range 9 West.

CHAINS

magnetic declination, $20^{\circ} 45'$ E.

- Thence S. $89^{\circ} 53'$ W., resurveying the S. bdy. of sec. 36.
Descend NW. slope, through heavy timber and dense undergrowth.
Top of spur, slopes NW.; continue descent.
- 10.60
- 18.27 Intersect the closing cor. of Tps. 33 S., Rs. 8 and 9 W., which is a sandstone, 5x8x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor, (viz.: 6 notches on E., W., and S. edges, from which
- A fir, 10 ins. diam., bears S. 78° E., 46 lks. dist.,
marked T33S R8W S6 BT.
- A pine, 30 ins. diam., bears S. 30° W., 29 lks. dist.,
marked T33S R9W S1 BT.)
- 22.10 Creek, 6 lks. wide, course SW.; along S. slope.
- 37.15 Creek, 3 lks. wide, course S.
- 39.06 Intersect the old standard $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to an angle point and perpetuate it as follows: alongside the old cor.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,
for angle point, with brass cap marked
- A P
1917
- from which
- A laurel, 20 ins. diam., bears N. 7° E., 48 lks. dist.,
marked AP BT. (Old B. T.)
- A fir, 20 ins. diam., bears N. 35° W., 42 lks. dist.,
marked AP BT. (Old B. T.)
- Thence S. $89^{\circ} 51'$ W., continuing my measurements
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,
for standard $\frac{1}{4}$ sec. cor., with brass cap marked
- S C
 $\frac{1}{4}$ S 36
1917
- from which
- A fir, 10 ins. diam., bears N. 50° E., 34 lks. dist.,
marked SC $\frac{1}{4}$ S36 BT.
- A laurel, 5 ins. diam., bears N. 76° W., 31 lks. dist.,
marked SC $\frac{1}{4}$ S36 BT.
- 57.60 Top of spur, slopes S.; descend.
- 68.15 Creek, 2 lks. wide, course S.
- 78.09 Intersect the point for old standard cor. of secs. 35 and 36, located by reference to the bearing trees as described by the surveyor general; all other traces of the cor. have disappeared. I change this cor. to an angle point and perpetuate it as follows: at the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,
for angle point, with brass cap marked
- A P
1917
- from which
- A laurel, 16 ins. diam., bears N. 26° E., 17 lks. dist.,