

## County Surveyor's Record, Douglas County, Oregon

15

## Resurvey of 7th Standard Parallel South, through Range 9 West

CHAINS

for standard  $\frac{1}{4}$  sec. cor., with brass cap marked
$$\begin{array}{c} S C \\ \frac{1}{4} S 34 \end{array}$$

1917

from which

A fir, 36 ins. diam., bears N. 15° E., 73 lks. dist.,  
marked SC  $\frac{1}{4}$  S34 BT.

A laurel, 16 ins. diam., bears N. 69° W., 59 lks. dist.,  
marked SC  $\frac{1}{4}$  S34 BT.

- 44.00 Descend steep slope.
- 59.00 Top of bluff, 100 ft. high.
- 60.50 Kelsey Creek, 30 lks. wide, course S.; ascend steep SE. slope.
- 67.00 Top of steep ascent; ascend gradual slope.
- 71.87 The point for old standard cor. of secs. 33 and 34, located by reference to the bearing trees as described by the surveyor general, bears North, 1 lk. dist. As the land to both the N. and S. of this cor. is unsurveyed, I destroy all traces of the cor.
- 72.10 Creek, 1 lk. wide, course SE.; ascend.
- 77.25 Top of spur, slopes SE.; descend.
- 78.30 Creek, 1 lk. wide, course SE.; ascend.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for standard cor. of secs. 33 and 34, with brass cap marked.
- $$\begin{array}{c} S C \\ T32S | R9W \\ \hline S 33 | S 34 \end{array}$$
- 1917
- from which
- A fir, 48 ins. diam., bears N. 12° E., 55 lks. dist.,  
marked SC T32S R9W S34 BT.
- A tan oak, 24 ins. diam., bears N. 47° W., 56 lks. dist.,  
marked SC T32S R9W S33 BT.
- Land, mountainous. Soil, rocky clay loam and shale rock, 3rd and 4th rate. Timber, fir, sugar pine, laurel and live oak. Undergrowth, buckhorn, live oak and laurel.
- 
- S. 89° 52' W., resurveying S. bdy. of sec. 33.
- Ascend SE. slope, through heavy timber and dense undergrowth.
- 10.45 Creek, 2 lks. wide, course SE.; continue ascent.
- 12.50 Leave heavy timber, bears N. and S.
- 15.00 Top of brushy spur, slopes S.; descend.
- 22.95 Creek, 4 lks. wide, course S.; enter heavy timber, bears N. and S. ascend.
- 29.54 The point for the old standard cor.,  $\frac{1}{4}$  sec. cor., located by reference to the bearing trees as described by the surveyor general, bears North, 11 lks. dist. The cor. stone, which is a basalt, 15x12x12 ins., I find lying loose on the ground some distance from the true cor. point. As the land to both the N. and S. of this cor. is unsurveyed, I destroy all traces of it.