

County Surveyor's Record, Douglas County, Oregon

16

Resurvey of 7th Standard Parallel South, through Range 9 West.

CHAINS

- 33.00 Top of spur, slopes SE.; descend.
- 37.90 Dry ravine, course SE.; ascend.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap marked
- S C
 $\frac{1}{4}$ S 33
1917
- from which
- A fir, 72 ins. diam., bears N. 3° E., 131 lks. dist., marked SC $\frac{1}{4}$ S33BT.
- A fir, 28 ins. diam., bears N. 82° W., 36 lks. dist., marked SC $\frac{1}{4}$ S33 BT.
- 46.40 New trail under construction, bears N. and S.
- 52.50 Top of spur, slopes SE.; descend.
- 53.50 Ravine, course SE.; ascend.
- 67.14 The old standard cor. of secs. 32 and 33, which is a decayed post, marked and witnessed as described by the surveyor general (SW. and NW. bearing trees as described,) bears North, 1 lk. dist. As the land to both the N. and S. of this cor. is unsurveyed, I destroy all traces of it.
- 72.80 Trail, to H. Jones' place, bears N. and S. Ravine, course S.; continue ascent.
- 79.00 Top of ridge, bears NE. and SW. County trail, Dothan to Gold Beach, bears NE. and SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for standard cor. of secs. 32 and 33, with brass cap marked
- S C
T32S | R9W
S 32 | S 33
1917
- from which
- A chinquapin, 18 ins. diam., bears N. 5° E., 62 lks. dist., marked SC T32S R9W S33 BT.
- A fir, 36 ins. diam., bears N. 35° W., 32 lks. dist., marked SC T32S R9W S32 BT.
- Land, mountainous. Soil, stony clay loam and shale rock, 2nd, 3rd and 4th rate. Timber, fir, sugar pine, chinquapin and laurel. Undergrowth, tan oak, chinquapin, laurel and buckhorn.
-
- S. 89° 52' W., resurveying S. bdy. of sec. 32.
- Descend NW. slope, through heavy timber and dense undergrowth.
- 6.50 Head of a ravine, course NW.; ascend E. slope.
- 17.40 Top of ridge, bears NW. and SE.; descend. County trail, Dothan to Gold Beach, bears NW. and SE.
- 19.20 Intersect the closing cor. of secs. 4 and 5, T. 33 S., R. 9 W., which is a basalt stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.
- Thence S. 89° 54' W., continuing my measurements
- 27.14 Intersect the old standard $\frac{1}{4}$ sec. cor., which is a basalt stone,