

Resurvey of 7th Standard Parallel South, through Range 9 West

CHAINS

4x12x8 ins. above ground, loosely set, marked and witnessed as described by the surveyor general. I change this cor. to an angle point and perpetuate it as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for angle point, with brass cap marked

A P

1917

from which

A fir, 36 ins. diam., bears N. 77° E., 32 lks. dist., marked AP BT. (Old B. T.)

A fir, 36 ins. diam., bears N. 11° W., 9 lks. dist., marked AP BT. (Old B. T.)

Thence S. 89° 38' W., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap marked

S C

$\frac{1}{4}$ S 32

1917

from which

A laurel, 6 ins. diam., bears N. 64° E., 29 lks. dist., marked SC $\frac{1}{4}$ S32 BT.

A laurel, 4 ins. diam., bears N. 40° W., 36 lks. dist., marked SC $\frac{1}{4}$ S32 BT.

Along S. slope.

46.20 Creek, 1 lk. wide, course S.

67.20 Intersect the old standard cor. of secs. 31 and 32, which is a basalt stone, 14x12x12 ins., loosely set, marked and witnessed as described by the surveyor general, except that the bearing trees on the N. are dead. I change this cor. to an angle point and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for angle point, with brass cap marked

A P

1917

from which

A fir, 48 ins. diam., bears N. 63° E., 56 lks. dist., marked AP BT. (New B. T.)

A fir, 20 ins. diam., bears N. 84° W., 104 lks. dist., marked AP BT. (New B. T.)

Thence S. 89° 48' W., continuing my measurements

72.00 Ascend gentle SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for standard cor. of secs. 31 and 32, with brass cap marked

S C

T32S | R9W
S 31 | S 32

1917

from which

A cedar, 9 ins. diam., bears N. 77 $\frac{1}{2}$ ° E., 64 lks. dist., marked SC T32S R9W S32 BT.

A fir, 8 ins. diam., bears N. 41° W., 45 lks. dist.,