

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the North Boundary and Partial
 Subdivision of T. 27 S., R. 2 W.
 Executed by Harold D. Corbin, Cadastral Surveyor
 Under Special Instructions dated June 21, 1957.

CHAINS

Dependent Resurvey of Portion of North Boundary of T. 27 S., R. 2 W., Willamette Meridian, Oregon.
 (Restoring the 1882 Survey by Samuel C. Flint and the Retracement in 1913 and 1914 by Charles M. Collier)

Beginning at the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a basalt stone, 13x8x8 ins., 8 ins. above ground, firmly set, marked with 2 grooves on the east and 4 grooves on the west face, from which the remains of the original bearing trees, as follows:

A madrone, 7 ins. diam., bears N. 57° E., 71 lks. dist., with scribe marks BT visible on opened blaze.

A madrone, 9 ins. diam., bears S. 82° E., 84 lks. dist., with healed blaze facing the cor.

A fir stump, 36 ins. diam., bears S. 75° W., 57 lks. dist., with healed blaze facing the cor.

A fir, 36 ins. diam., bears N. 68° W., 55 lks. dist., with healed blaze facing the cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T26S R2W
 S 34 | S 35
 S 3 | S 2
 T27S
 1957.

from which

A fir, 13 ins. diam., bears N. 25½° E., 39 lks. dist., marked T26S R2W S35 BT.

A fir, 13 ins. diam., bears S. 43° E., 75 lks. dist., marked T27S R2W S2 BT.

A fir, 13 ins. diam., bears S. 29¼° W., 87 lks. dist., marked T27S R2W S3 BT.

A white fir, 10 ins. diam., bears N. 76° W., 112 lks. dist., marked T26S R2W S34 BT.

Deposit original cor. stone alongside iron post.

N. 89° 37' W., between secs. 3 and 34, marking and blazing true line.

Descend 381 ft. along S. slope, changing to SW. slope through heavy timber and dense undergrowth.

- 13.35 Logging road, 20 lks. wide, bears N. 40° W. and S. 40° E.
- 25.88 Spring branch, 3 lks. wide, course S.; asc. 253 ft. over SE. slope.
- 31.40 Skid road, 20 lks. wide, bears NE. and SW.
- 34.01 Spur, slopes S.; descend 176 ft. over SW. slope.
- 39.75 The ¼ sec. cor. of secs. 3 and 34, monumented with a basalt stone, 20x10x8 ins., 10 ins. above ground, firmly set, marked ¼ on the N. face, from which the remains of the original bearing trees, as follows:
 - A fir, 42 ins. diam., bears N. 10° W., 15 lks. dist., with a healed blaze facing the cor.
 - A fir, 38 ins. diam., bears S. 10° W., 30 lks. dist., with