

Dependent Resurvey of Portion of North Boundary, T. 27 S., R. 2 W.

CHAINS

healed blaze facing the cor.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

T26S R2W

1	S	34
4	S	3

T27S

from which

A madrone, 11 ins. diam., bears N.  $49\frac{1}{2}^{\circ}$  E., 66 lks. dist., marked  $\frac{1}{4}$  S34 BT.A fir, 50 ins. diam., bears S.  $23\frac{1}{2}^{\circ}$  W., 77 lks. dist., marked  $\frac{1}{4}$  S3 BT.S.  $87^{\circ} 23'$  W., beginning new measurement.

Descend 632 ft. over SW. slope.

20.09 Creek, 5 lks. wide, course S.; ascend 637 ft. over east slope.

33.62 Spur, slopes S.; descend 46 ft. over SW. slope.

38.45 The cor. of secs. 3, 4, 33 and 34, monumented with a cedar post, 4 x 4 ins. in cross section, 18 ins. above ground, firmly set, mkd. T26S S34 on north, R2W on south, T27S S3 on east, and S33 on west face; from which the original bearing trees, as follows:

A fir, 38 ins. diam., bears N.  $40^{\circ}$  E., 21 lks. dist., with scribe marks T26 R2W S34 visible on opened blaze.A madrone, 10 ins. diam., bears S.  $78\frac{1}{2}^{\circ}$  E., 33 lks. dist., with scribe marks T27S R2W visible on opened blaze.A fir, 48 ins. diam., bears S.  $78\frac{1}{2}^{\circ}$  W., 76 lks. dist., with a healed blaze.A fir, 46 ins. diam., bears N.  $72^{\circ}$  W., 33 lks. dist., with scribe marks R2W visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked.

T26S R2W

S	33		S	34
S	4		S	3

T27S

1957

from which

A madrone, 14 ins. diam., bears N.  $71\frac{3}{4}^{\circ}$  E., 82 lks. dist., marked T26S R2W S34 BT.A fir, 17 ins. diam., bears S.  $33\frac{1}{4}^{\circ}$  E., 39 lks. dist., marked T27S R2W S3 BT.A fir, 6 ins. diam., bears S.  $31^{\circ}$  W., 83 lks. dist., marked T27S R2W S4 BT.A fir, 9 ins. diam., bears N.  $27\frac{1}{2}^{\circ}$  W., 30 lks. dist., marked T26S R2W S33 BT.