

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of North Boundary of T. 27 S., R. 2 W.

CHAINS

Deposit cedar stake alongside iron post.

Land, mountainous. Soil, stony clay. Timber, fir, pine, cedar, maple and madrone; undergrowth, vine maple, salal, hazel, ocean spray, and poison oak.

Dependent Resurvey of Portion of Subdivisional Lines, T. 27 S., R. 2 W.

(Restoring the 1882 Survey by Samuel C. Flint and the 1905 and 1907 Survey and Retracements by Charles E. Roberts)

From the cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 12x9x6 ins., 8 ins. above ground, firmly set, with 5 notches on the south and 2 notches on the east edge, from which the remains of the original bearing trees, as follows:


A fir stump, 36 ins. diam., bears N. 19° E., 83 lks. dist., with a healed blaze.

A dead fir, 32 ins. diam., bears S. 50° E., 94 lks. dist., with B and other illegible scribe marks visible on opened blaze.

A cedar, 24 ins. diam., bears N. 59° W., 75 lks. dist., with T27 R2W S3 BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



FD OK BY GEISLER  
A/84 M 90-55

from which

A fir, 6 ins. diam., bears N. 60° E., 87 lks. dist., marked T27S R2W S2 BT.

A cedar, 5 ins. diam., bears S. 28½° E., 30 lks. dist., marked T27S R2W S11 B<sup>I</sup>.

A sugar pine, 5 ins. diam., bears S. 27° W., 28 lks. dist., marked T27S R2W S10 BT.

A fir, 8 ins. diam., bears N. 57½° W., 33 lks. dist., marked T27S R2W S3 BT.


N. 0° 25' E., bet. secs. 2 and 3, marking and blazing the true line.

Descend 204 ft. over N. slope through heavy timber and dense undergrowth.

19.27

Point for the S 1/16 sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked



from which