

## County Surveyor's Record, Douglas County, Oregon

5

Dependent Resurvey of Portion of Subdivisional Lines of T. 27 S., R. 2 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked
$$\begin{array}{c} T27S R2W \\ \hline S 9 | S 10 \\ \hline S 16 \\ 1957 \end{array}$$

from which

A white fir, 13 ins. diam., bears N.  $33^\circ$  E., 65 lks. dist., marked T27S R2W S10 BT.A fir, 13 ins. diam., bears S.  $26\frac{1}{2}^\circ$  W., 40 lks. dist., marked T27S R2W S16 BT.A fir, 18 ins. diam., bears N.  $20^\circ$  W., 62 lks. dist., marked T27S R2W S9 BT.

Deposit original cor. stone alongside iron post.

N.  $0^\circ 13'$  E., between secs. 9 and 10.

Descend 316 ft. over NE. slope, changing to N. slope through heavy timber and dense undergrowth.

3.75 Maintained and graveled logging road, 40 lks. wide, bears N.  $60^\circ$  E. curving to N. and S.  $60^\circ$  W. curving to W.

22.72 Spring seepage, course west; descend 8 ft. over NW. slope.

24.92 Spring branch, 3 lks. wide, course W.; desc. 17 ft. over NW. slope.

27.70 Spring branch, 2 lks. wide, course W.; desc. 47 ft. over NW. slope.

33.35 Spring seepage, course W.; desc. 6 ft. over NW. slope.

35.25 Spring seepage, course W.; desc. 31 ft. over NW. slope.

39.99 The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, monumented with a bsalt stone, 14x8x5 ins., 10 ins. in the ground, firmly set, with  $\frac{1}{4}$  chiseled on the W. face, from which the remains of the original bearing trees as follows:A rotted and burned madrone snag, 10 ins. diam., bears S.  $37^\circ$  E., 22 lks. dist., with an opened and rotted blaze, no scribe marks visible.A white fir, 22 lks. diam., bears S.  $73\frac{3}{4}^\circ$  W., 22 lks. dist., with illegible scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked
$$\begin{array}{c} T27S R2W \\ \hline \frac{1}{4} \\ \hline S 9 | S 10 \\ \hline 1957 \end{array}$$

from which

A fir, 20 ins. diam., bears S.  $54\frac{1}{2}^\circ$  E., 74 lks. dist., marked  $\frac{1}{4}$  S10 BT.A cedar, 9 ins. diam., bears N.  $40^\circ$  W., 70 lks. dist., marked  $\frac{1}{4}$  S9 BT.