

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 27 S., R. 2 W.

CHAINS

Deposit original corner stone alongside iron post.

N. 0° 08' W., beginning new measurement.

Descend 64 ft. over NW. slope.

4.08 Spring branch, 4 lks. wide, course W.; desc. 1 ft. along W. slope.

6.58 Spring branch, 2 lks. wide, course W.; desc. 230 ft. along W. slope, changing to NW. slope.

32.67 Corner of woven-wire fence with fences extending S. and S. 40° W.

34.21 Little River, 40 lks. wide, course S. 70° W.; asc. 29 ft. over SE. slope.

35.35 Asphaltic road, 30 lks. wide, bears N. 70° E. and S. 70° W.

37.95 From this point, the NW. cor. of wood frame machine shop, bears E. 18 lks. dist., dimensions 44 x 107 ft., long side bears S.

39.15 From this point, the NW. cor. of wood frame dwelling bears E. 60 lks. dist., dimensions 54 x 71 ft., long side bears E.

40.635 The original closing corner of secs. 9 and 10, perpetuated by Ben B. Irving, county surveyor, in 1929, with a galvanized iron pipe, 2 ins. diam., 18 ins. above ground, firmly set, at record distance from the original bearing trees, as follows:

A fir stump, 30 ins. diam., bears S. 78½° E., 48 lks. dist., with illegible scribe marks visible on opened blaze. (Record bearing S. 80½° E.)

A fir stump, 30 ins. diam., bears S. 63½° W., 120 lks. dist., with scribe marks T27S 2W visible on opened blaze. (Record bearing S. 63° W.)

and trees established by county surveyor

A fir, 10 ins. diam., bears S. 17° E., 80 lks. dist., with scribe marks 10 T27S R2W CS visible on opened blaze.

A fir stump, 9 ins. diam., bears S. 52° W., 61 lks. dist., with scribe marks S9 T27S R2W CS BT visible on opened blaze.

A fir, 14 ins. diam., bears N. 74° W., 108 lks. dist., marked CS S4 T27S R2 visible on opened blaze.

40.80 Intersect the south boundary of sec. 3, true point for closing cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T27S R2W  
S 3  
— S 9 | S 10  
C C  
1957

from which

A fir, 10 ins. diam., bears S. 4° E., 125 lks. dist., marked T27S R2W S10 CC. BT.

A fir, 15 ins. diam., bears S. 38° W., 172 lks. dist., marked T27S R2W S9 CC. BT.