

## County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey of Portion of Subdivisional Lines of T. 27 S., R. 2 W.

CHAINS	<p>From this point the cor. of secs. 3 and 4, only, on the N. bdy. of sec. 9 bears S. 88° 56' W., 123 lks. dist.</p> <p>Land, rolling hills. Soil, stony clay and loam. Timber, fir, cedar, scattering pine, ash, alder and maple; undergrowth, vine maple, poison oak, fern and salal.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89° 14' W., along south bdy. of sec. 3.</p> <p>Ascend 122 ft. over NE. slope through heavy timber and dense undergrowth.</p> <p>13.60 Spur, slopes NW.; descend 155 ft. over NW. slope.</p> <p>24.13 Ravine, course N.; descend 98 ft. over NW. slope.</p> <p>40.48 Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 3, only, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, and in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with brass cap marked</p> <p style="text-align: center;">T27S R2W <u><math>\frac{1}{4}</math> S 3</u> 1957</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears N. <math>3\frac{1}{2}</math>° E., 12 lks. dist., marked <math>\frac{1}{4}</math> S3 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 61° W., 43 lks. dist., mkd. <math>\frac{1}{4}</math> S3 BT.</p> <hr/> <p>S. 88° 56' W., beginning new measurement.</p> <p>Descend 14 ft. over NW. slope.</p> <p>1.12 Creek, 10 lks. wide, course NW.; descend 2 ft. over NW. slope.</p> <p>1.85 Creek, 3 lks. wide, course NW.; descend 13 ft. over NW. slope.</p> <p>3.80 Creek, 2 lks. wide, course NW.; ascend 79 ft. over E. slope, changing to NE. slope.</p> <p>14.40 Spur, slopes N. 20° E.; descend 216 ft. over NW. slope, changing to W. slope.</p> <p>16.66 Graveled and maintained road, 30 lks. wide, bears NE. and SW. curving to west.</p> <p>20.27 Point for the W <math>\frac{1}{16}</math> sec. cor. of sec. 3, only.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">W <math>\frac{1}{16}</math> S 3 1957</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 19° E., 34 lks. dist., marked W<math>\frac{1}{16}</math> S3 BT.</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears N. <math>27\frac{1}{2}</math>° W., 6 lks. dist., marked W<math>\frac{1}{16}</math> S3 BT.</p> <p>Descend 10 ft. over SW. slope.</p> <p>21.65 Ravine, course N. 70° W.; descend 111 ft. over NW. slope.</p> <p>23.95 Left bank of Little River, bears N. 45° E. and S. 45° W., course SW.</p> <p>24.25 Right bank of Little River; ascend 23 ft. over general E. slope.</p>
--------	--