

Dependent Resurvey of Portion of Subdivisional Lines of T. 27 S., R. 2 W.

CHAINS	
30.32	From this point, the NW. cor. of a wood frame dwelling bears S. 22° 53' W., 122 lks. dist., dimensions 34 x 31 ft., long side bears SE.
31.00	Asphaltic road, 40 lks. wide, bears N. 25° E. and S. 25° W., curving to west.
32.32	From this point, the SE. cor. of the southerly of four wood frame dwellings bears N. 34° 49' E., 72 lks. dist., dimensions of each dwelling 41 x 32 ft., 40 ft. apart with the row of buildings bearing N. 30° E. From this same point, the NE. cor. of a wood frame building bears S. 26° 04' W., 127 lks. dist., dimensions 24 x 18 ft., long side bears S. From this same point, the NE. cor. of a wood frame building bears S. 33° 07' W., 95 lks. dist., dimensions 20 x 16 ft., long side bears S.
33.10	Graveled and maintained road, 20 lks. wide, bears N. 25° E. and S. 25° W.
34.32	From this point, the SE. cor. of the southerly of four wood frame dwellings bears N. 36° 09' E., 46 lks. dist., dimensions of each dwelling 41 x 32 ft., 40 ft. apart with the row of buildings bearing N. 30° E. From this same point, the NE. cor. of a wood frame building bears S. 7° 18' E., 50 lks. dist., dimensions 44 x 36 ft., long side bears S.
37.32	From this point the NW. cor. of a wood frame shed bears S. 53° 33' E., 32 lks. dist., dimensions 36 x 22 ft., long side bears E. From this same point, the NE. cor. of a wood frame building bears S. 16° 51' E., 136 lks. dist., dimensions 69 x 53 ft., long side bears W. From this same point, the SW. cor. of a wood frame building bears S. 50° 18' E., 198 lks. dist., dimensions 84 x 52 ft., long side bears E. From this same point, the NE. cor. of a wood frame cabin bears S. 42° 54' W., 114 lks. dist., dimensions 22 x 12 ft., long side bears S.
39.31	The closing cor. of secs. 9 and 10.
40.54	Point for the cor. of secs. 3 and 4, only, on the N. bdy. of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked <div style="text-align: center;"> T27S R2W <u>S 4 S 3</u> S 9 1957 </div> from which A fir, 6 ins. diam., bears N. 42½° E., 65 lks. dist., marked T27S R2W S3 BT. A cedar, 13 ins. diam., bears N. 19° W., 102 lks. dist.,