

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 27 S., R. 2 W.

CHAINS

marked T27S R2W S4 BT.

Land, rolling hills. Soil, sandy clay and loam. Timber, fir, cedar, ash, alder and scattering madrone and maple; undergrowth, vine maple, mock orange, snowberry, poison oak, fern and salal.

N. 1° 20' E., between secs. 3 and 4.

Ascend 123 ft. over SE. slope through heavy timber and dense undergrowth.


4.68 Graveled and maintained road, 40 lks. wide, bears E. and W.

11.00 Top of ascent, slopes E., also a circular water storage tank, 29 ft. in diam., on line; descend 62 ft. over NE. slope.

21.14 Creek, 5 lks. wide, course E.; ascend 5 ft. over SE. slope.

21.96 Point for the S 1/16 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.



from which

A hemlock, 10 ins. diam., bears S. 88½° E., 63 lks. dist., marked S 1/16 S3 BT.

A maple, 12 ins. diam., bears N. 45° W., 20 lks. dist., marked S 1/16 S 4 BT.

Ascend 154 ft. over S. slope.

26.15 Logging road, 25 lks. wide, bears NE. and SW.

27.72 Spur, slopes SE.; descend 84 ft. over NE. slope.

29.46 Creek, 5 lks. wide, course SE.; ascend 262 ft. over S. slope.


43.92 The ¼ sec. cor. of secs. 3 and 4, monumented with a basalt stone, 18 x 18 x 6 ins., 10 ins. in the ground, firmly set, marked ¼ on the S. face, from which the remains of the original bearing trees, as follows:

A fir, 27 ins. diam., bears S. 28° E., 19 lks. dist., with a healed blaze, also bark scribed S CS BT.

A fir, stump, 42 ins. diam., bears N. 35° W., 65 lks. dist., with scribe mark B visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked



from which

A fir, 12 ins. diam., bears N. 52° E., 43 lks. dist., marked ¼ S3 BT.