

## Mineral Survey No. 794

CHAINS  
Feet

## REPORT

The lode line was run directly upon the ground and the corners established by means of offsets from the lode line. The tie line was run directly upon the ground.

The NW. cor. sec. 4, T. 31 S., R. 5 W., of the W. M., is a pine post, 4 ins. sq., 3 ft. above ground, scribed T. 31 S. R. 5 W. S. 4 S. 5 T. 30 S. R. 5 W. S. 32 S. 33 C. S. (County Surveyor)

Near this corner post are 4 large laurels, one in each section, bearing old blazes and scribe marks, most of which are indistinct on account of fire and decay.

The W.  $\frac{1}{4}$  cor. sec. 4 is a post, 4 ins. sq., 3 ft. above ground, scribed  $\frac{1}{4}$  S. 4 and  $\frac{1}{4}$  S. 5; whence -

A fir, 18 ins. diam., blazed and scribed  $\frac{1}{4}$  S. B.T., bears N. 33°30' W., 8 ft. and

A cedar, 72 ins. diam., blazed and scribed  $\frac{1}{4}$  S. B.T., bears S. 65°40' W., 35.5 ft.

The N.  $\frac{1}{4}$  cor. sec. 4 could not be identified.

Survey No. 37 D.A. Levens Gold Quartz Claim.

The NE. corner is a post scribed MS. 37. Near it are four witness trees each blazed and scribed B.T. M.S. 37.

The SE. corner is a post bearing partly obliterated scribe marks. Near it are two witness trees each scribed M.S. and bearing other illegible scribe marks.

Both of these corners and their witness trees have been partly destroyed by fire and decay.

I find the line between these corners to be S. 24° E., 150 ft., as approved. I find the connection line to be N. 73°16' E., 1123.63 ft. instead of N. 71°25' E., 16.95 chs. as given in the supplemental field notes of the connection line survey made Sept. 15, 1880.