

## County Surveyor's Record, Douglas County, Oregon

2

Dependent Resurvey of a Portion of the 6th Stan. Par. S., S. Bdy.  
T. 27 S., R 4 W.

CHAINS

bark scribed S34.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

S C  
T27S R4W  
S 34 S35

1958

from which

A cedar, 13 ins. diam., bears N.  $59^\circ$  E., 110  $\frac{3}{4}$  lks. dist., marked T27S R4W S35 SC BT.A cedar, 13 ins. diam., bears N.  $29\frac{3}{4}$  W., 59  $\frac{1}{4}$  lks. dist., marked T27S R4W S34 SC BT.N.  $89^\circ 26'$  W., along S. bdy. of sec. 34, marking and blazing the true line.

Descend 4 ft. over NW. slope through heavy timber and dense undergrowth.

0.595 Point for the closing cor. of secs. 2 and 3, on the N. bdy. T. 28 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

T27S R4W  
S 34  
S 3 S 2  
T28S R4W  
C C  
1958

from which

A fir, 40 ins. diam., bears S.  $30\frac{1}{2}^\circ$  E., 54  $\frac{1}{4}$  lks. dist., marked T28S R4W S2 CC BT.A fir, 6 ins. diam., bears S.  $50^\circ$  W., 46  $\frac{1}{4}$  lks. dist., marked T28S R4W S3 CC BT.

Descend 9 ft. over NW. slope.

1.95 Spring branch, 2 lks. wide, course N.; ascend 126 ft. over NE. slope.

3.05 Leave timber, enter logged area, edge bears N. and S.

12.60 Spur, slopes N.; descend 59 ft. along general N. slope.

20.265 Point for E 1/16 sec. cor. of secs. 3 only, on N. bdy. of T. 28 S., R. 4 W.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

E 1/16 S 3  
1958

from which

A fir, 13 ins. diam., bears S.  $29\frac{3}{4}^\circ$  E., 202 lks. dist.,