

Dependent Resurvey of a Portion of the 6th Stan. Par. S., S. Bdy.  
T. 27 S., R. 4 W.

CHAINS	<p>marked E 1/16 S3 BT.</p> <p>A fir, 45 ins. diam., bears S. 37° W., 455 lks. dist., marked E 1/16 S3 BT.</p> <p>Descend 126 ft. over general N. slope.</p>
39.59	<p>Point for the standard <math>\frac{1}{4}</math> sec. cor. of sec. 34 only, at proportionate distance; there is no remaining evidence of the Original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">S C T27S R4W <u><math>\frac{1}{4}</math> S 34</u> 1958</p> <p>from which</p> <p>A fir, 15 ins. diam., bears N. <math>49\frac{1}{2}^\circ</math> W., 299 lks. dist., marked <math>\frac{1}{4}</math> S34 SC BT.</p> <p>Raise a mound of stone, 3 ft. base, <math>1\frac{1}{2}</math> ft. high N. of corner.</p> <p>Ascend 2 ft. along N. slope.</p>
39.935	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 3 only, on the N. bdy. T. 28 S., R4W., at midpoint on the N. bdy. of sec. 3.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap marked</p> <p style="text-align: center;"><u><math>\frac{1}{4}</math> S 3</u> T28S R4W 1958</p> <p>from which</p> <p>A fir, 13 ins. diam., bears S. 80° E., 441 lks. dist., marked <math>\frac{1}{4}</math> S3 BT.</p> <p>Raise a mound of stone, 3 ft. base, <math>1\frac{1}{2}</math> ft. high, south of the corner.</p> <p>From this point the SW. cor. of an abandoned wood frame dwelling, bears N. 8° 37' E., 8.52 chs. dist.</p> <p>Descend 14 ft. over N. slope.</p>
40.53	Dirt road, 20 lks. wide, bears NW. and SE.
44.50	Dry creek bed, 3 lks. wide, course N.; desc. 4 ft. along N. slope.
49.60	Foot of descent, slopes N.; asc. 164 ft. over NE. slope changing to E. slope.
64.90	Ridge, bears N. and S.; descend 330 ft. over W. slope.
66.00	Dirt access road, 15 lks. wide, bears N. 20° W. and S. 20° E.
79.275	The standard cor. of secs. 3, 4, 33 and 34, determined at record bearing and distance from the only remaining original bearing tree marked by Addison Flint in 1855, which was remarked by F. C. Frear, D.C.S., in 1918, as follows: